

ZR57KCE-TF5

HFC, R-407C, 60 Hz, 3 -Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (Btu/hr)	56200	67100
Power (W):	5110	3610
Current (Amps):	15.85	12.65
EER (Btu/Wh):	11.00	18.60
Mass Flow (lbs/hr):	812	829
<u>Sound Data @</u>		
Sound Power (dBA):	74 Avg	79 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2014-08-05	

Electrical

LRA-High*(Amp):	124.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	24.1
Max Operating Current(Amp):	26.0
RLA, MCC/1.4;use for contactor selection (Amp):	17.2
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	15.4
RPM:	3500
UL File No:	SA-2337
UL File Date:	1993-07-26
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment(in ³ /Rev):	4.71
Displacment(ft ³ /hr):	572.40
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	17.75
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	18.00 *
Suction Size (in),Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	66
Oil Recharge (oz):	62
Net Weight (lbs):	80.0
Internal Free Volume (in ³):	256.0
Horse Power:	4.75
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-407C HFC	200/220	3	50	Air Conditioning