

Product Family

2" CladLite® Pads

Equipment Pads



Description

CladLite® Equipment Pads provide the strength and durability customers demand in an easy to install pad. CladLite® Pads are up to 80% lighter than solid concrete but still provide rock solid support for equipment. Once it's set, so are you. CladLite® Pads stay in place and can withstand anything mother nature can throw at them. These pads provide superior resistance to sun, moisture, and freeze-thaw conditions. And the vibration dampening EPS foam core is unaffected by water, soil, fungus or bacteria. The 2" thick CladLite® pad is the choice for equipment pads, unless a thicker pad (3") is required by the local building code.

1636-2

Features

- 125 lbs. per 2" diameter foot
- 80% lighter than solid concrete
- Continuous steel reinforcement
- Full foam bottom resists settling and vibration
- Impervious to weather

Specifications

Warranty:

Limited Lifetime Warranty

Performance:

Flawless performance under the 25-cycle regimen specified by ASTM C67

Chemical Resistance:

Does not craze, soften, delaminate, or spall when tested per ASTM D2299 with the following:

- R-22 and R-134a
- Compressor oil
- Synthetic canine urine
- Salt solution, 20% by volume

Foam Core:

ASTM Type 1 EPS

Flame Resistance:

Cladding resists compressor heat and incidental torch contact. Not to be used under heating devices.

STOCK NO	Material	Size	Thickness	Estimated Allowable Load	Weight
1636-2	Concrete/Foam	16x36	2 in	70 lbs	39 lbs
2424-2	Concrete/Foam	24x24	2 in	173 lbs	30.16 lbs
2436-2	Concrete/Foam	24x36	2 in	259 lbs	61 lbs
2442-2	Concrete/Foam	24x42	2 in	302 lbs	57 lbs
2454-2	Concrete/Foam	24x54	2 in	531 lbs	84 lbs
26-2	Concrete/Foam	26 Round	2 in	205 lbs	33 lbs
2626-2	Concrete/Foam	26x26	2 in	205 lbs	43 lbs
2660-2	Concrete/Foam	26x60	2 in	410 lbs	95 lbs
30-2	Concrete/Foam	30 Round	2 in	270 lbs	36 lbs
3030-2	Concrete/Foam	30x30	2 in	270 lbs	42.72 lbs
3036-2	Concrete/Foam	30x36	2 in	324 lbs	52.84 lbs
3040-2	Concrete/Foam	30x40	2 in	360 lbs	70 lbs
3143-2	Concrete/Foam	31x43	2 in	577 lbs	71.16 lbs
32-2	Concrete/Foam	32 Round	2 in	307 lbs	44 lbs
3232-2	Concrete/Foam	32x32	2 in	307 lbs	50.96 lbs
3434-2	Concrete/Foam	34x34	2 in	347 lbs	52.84 lbs
3636-2	Concrete/Foam	36x36	2 in	389 lbs	62.88 lbs
3640-2	Concrete/Foam	36x40	2 in	423 lbs	70.92 lbs
3648-2	Concrete/Foam	36x48	2 in	518 lbs	87.84 lbs
3654-2	Concrete/Foam	36x54	2 in	589 lbs	93 lbs
3842-2	Concrete/Foam	38x42	2 in	479 lbs	87 lbs
4147-2	Concrete/Foam	41x47	2 in	560 lbs	115 lbs



Simplify The Way You Work

6650 Sugarloaf Parkway, Duluth, GA 30097 Phone: 800-955-2222 Fax: 678-542-3700 www.diversitech.com

© 2016 Diversitech Corporation

All rights reserved.

Rev. 4/03/17

Page 1 of 1