


SUBMITTAL RECORD \_\_\_\_\_  
 JOB \_\_\_\_\_  
 LOCATION \_\_\_\_\_  
 SUBMITTED TO \_\_\_\_\_  
 SUBMITTAL PREPARED BY \_\_\_\_\_  
 APPROVED BY \_\_\_\_\_  
 DATE \_\_\_\_\_



# Submittal Form Cleats

## DYN-O-MATE Cleat


- DOM-CLT and DOM-PCLT for use with DOMJ & DOMH 20 gauge flanges for airtight duct connections.
- DOM-CLT is manufactured from 20 gauge galvanized steel 6" pieces.
- DOM-PCLT is extruded .070" PVC and designed for break away connection needs.




Item #	Code	Description
21250	DOMCLT	6in. Metal Cleat
21256	DOMCLTSS	6in. Stainless Steel Cleat
21252	DOMPCLT	6in. Plastic Cleat

## Quad Cleat

- DOM-QCLT & HDQC-PLUS are compatible with Dyn-O-Mate® J, Ductmate™ 35, CL Ward™ J, Ward Industries™ J, Hardcast™ flanges, TDC, TDF and TDX Connections, and is manufactured from 22 gauge steel.
- HDQC-PLUS is also available in stainless steel.
- HDQC-PLUS is recommended for high pressure, heavy duty transverse duct.



DOMQCLT




HDQC-PLUS


Item #	Code	Description
21259	DOMQCLT	Metal Quad Cleat
21269	HDQC-PLUS	Heavy Duty Quad Cleat Plus
13175	HDQCPLUS125	Heavy Duty Quad Cleat Plus (1/2 box qty)
21228	HDQC-PLUS-SS	Heavy Duty Quad Cleat Plus - Stainless

## TDC/TDF Cleat

- For use with TDC/TDF connection.
- TDC-2230/TDF-2230 is 22 gauge steel formed into lengths of 30" long and divided into five 6" cleats that are partially cut through allowing them to be easily separated into 6" pieces.
- TDF-PCLT is extruded .070" PVC and designed for break away connection needs.
- TDC-SS is manufactured from 304 Stainless Steel.



Dimensions		
	TDC	TDF
A	.400	.450
B	.840	.975
C	1.150	1.075



Breakaway

Item #	Code	Description
<b>30" Pieces</b>		
13230	TDC2230	6in. TDC (Pre-Scored Cleat)
13231	TDF2230	TDF 6in. Metal (Pre-Scored Cleat)
13233	TDC-SS	6in. TDC Stainless (Pre-Scored Cleat)
<b>6" Pieces</b>		
21253	TDFPCLT	TDF 6in. Plastic

## **Installation Recommendations**

1/2" to 2" sp - 1 piece on 24" centers  
 2" to 3" sp - 1 piece on 18" centers  
 4" to 6" sp - 1 piece on 12" centers  
 Over 10" sp - continuous cleat

Duro Dyne East Division, Bay Shore, NY  
 Duro Dyne Midwest Division, Hamilton, OH  
 Duro Dyne West Division, Fontana, CA  
 Duro Dyne Canada, Lachine, Quebec, Canada

631-249-9000 Fax: 631-249-8346  
 513-870-6000 Fax: 513-870-6005  
 562-926-1774 Fax: 562-926-5778  
 514-422-9760 Fax: 514-636-0328

www.durodyne.com E-mail: durodyne@durodyne.com



©2018 Duro Dyne Corporation  
 Printed in USA 11/18  
 BO050006