BLUE 4" Thermostats

4-square-inch display

Single Stage Applications

Programmable 5/1/1, 5/2 or Ø Day and Non-Programmable Dual Powered – Hardwired or Battery Powered Includes Wall Plate F61-2634



PROGRAMMABLE MODELS

1F80-0471 1H/1C 5/1/1, 5/2 or Ø Day Option

1F80ST-0471 1H/1C 5/1/1, 5/2 or Ø Day Option Selecto – Spanish Language Model



Programmable

NON-PROGRAMMABLE ONLY MODELS

1F86-0471 1H/1C

1F86ST-0471 1H/1C

Selecto - Spanish Language Model



Non-Programmable

Emerson BLUE 4" Features:

- Easy-to-Read 4-Square-Inch Blue Display
- Battery Power Monitor
- Millivolt and Hydronic Zone Valve Compatible
- Exclusive Cool Savings™

5-Year Warranty





BLUE[™] 4" Thermostats

|F86-0471/1F86ST-0471

• For Single Stage Applications • Programmable 5/1/1, 5/2 or Ø Day and Non-Programmable • Hardwired or Battery Powered

Blue 4" Features

Large, 4-square-inch blue display with easy-to-see characters

Configures as manual heat/cool, auto changeover, heat only or cool only

Exclusive Cool Savings™ feature saves energy during peak A/C demand periods

Hydronic 2 or 3 wire applications

Battery power monitor

Easy-access battery compartment 5-year warranty

Programming

Choice of 5/1/1, 5/2 or Ø day programmable (1F80-0471, 1F80ST-0471)

4 time and 4 temperature settings per program (heat & cool)

Energy savings up to 33%

Pre-programmed software simplifies time and temperature programming

Display

Large LCD with improved contrast for easier reading

Lighted display for easier low-light viewing

Comfort & Convenience

Permanent program retention during power loss

Indefinite setpoint Hold

Air filter change indicator (optional)

Simple "set-up" menu to activate optional features

Temporary temperature override two-hour minimum or until next program period (1F80-0471, 1F80ST-0471)

Soft-touch keypad

Display temperature recalibration (+/- 4°)

Performance

Dual-Powered...choice of battery-powered or hardwired, for all applications -2 AA batteries included

Selectable Energy **Management Recovery** (1F80-0471, 1F80ST-0471)

Meets ENERGY STAR® specifications (1F80-0471, 1F80ST-0471)

Meets California Building Code, Title 24 (1F80-0471, 1F80ST-0471)

Fast (FA), medium (ME) or slow (SL) heating cycle anticipation

Easy-to-wire terminal block

Compressor lockout protection

Millivolt compatible Electric heat option



Dimensions

4.4"W x 3.4"H x 1.2"D

Electrical Specifications

0 to 30 VAC, 50/60 Hz or DC

0.05 to 1.5 Amps (load per terminal)

2.5 Amps maximum load (all terminals combined)

Single Stage Systems Gas, Oil, Electric

Millivolt Systems

2 or 3 Wire Hydronic Zone Valve

Thermal Specifications

Setpoint Temperature Range: 45° to 90°F (7° to 32°C)

Rated Differential: 0.4° to 1.7°F with adjustable anticipation

Operating Ambient Temperature: 32° to 105°F (0° to 40°C)

Operating Humidity Range: 90% non-condensing maximum

Shipping Temperature Range: -40° to 150°F (-40° to 65°C)

Accessories

Wall Plate F61-2634 (6.5"W x 5"H) (Included with all models)

Thermostat Guard F29-0231

(For additional guard options refer to White-Rodgers catalog at www.white-rodgers.com)

For Additional Information

Visit www.white-rodgers.com

Single Multi- Stage Stage Pump		Programs	Model	Applications				Selectable Performance Features								Comfort and Convenience Features							
Stages Heat/Cool by System		Program Options	Model Number	Gas/Oil/ Electric	Comfort Alert	3 Wire Zone	Millivolt	Power Source	Auto Changeover	Programmable Fan	Energy Mgt. Recovery	Energy Star	Dual Fuel Option	Temperature Limits	Indoor Remote Sensor	Outdoor Remote Sensor	Lighted Display***	Audible Feedback	Cool Savings™	Daylight Savings Adjustment	Ignition Module Reset	Permanent Memory	
1/1		1/1	5/1/1, 5/2, Ø	1F80-0471	/		/	✓	В,Н	1		1	✓					/		/		<	1
1/1		1/1	5/1/1, 5/2, Ø	1F80ST-0471	1		✓	✓	В,Н	1		1	\					/		1		\	1
1/1		1/1	Ø	1F86-0471	1		✓	\	В,Н	1								/		1		✓	1
1/1		1/1	Ø	1F86ST-0471	/		1	1	В,Н	1								1		1		✓	1

B =Battery, H =Hardwired *** Optional Continuous Display Light w/Hardwire Connection



