

FireMaster® FastWrap XL



Datasheet Code 7-4-236 E

© 2009 Morgan Thermal Ceramics, a business within the Morgan Ceramics Division of The Morgan Crucible Company plc



APPLICATIONS

Fire Protection of ventilation ducting for up to 2 hours in accordance with ISO 6944, BS 476 part 24 and EN 1366-1 standards.

Please refer to our Ductwork Fire Protection Design and Installation Manual FM 5.0 for more details



DESCRIPTION

FireMaster® FastWrap XL is a flexible blanket composed of high temperature fibres classified for applications to 1200°C and fully encapsulated in a durable glass fibre reinforced aluminium foil facing for easy handling and installation.

The foil encapsulation of the blanket prevents water, moisture or grease ingress ensuring good integrity and avoiding promotion of mould growth.

The core fibres in FastWrap XL are manufactured using Morgan Thermal Ceramics patented Superwool® fibre which is an alkaline earth silicate wool with low biopersistence exonerated from carcinogenic classification under Nota Q of the European Union Directive 97/69/EC

PRODUCT FEATURES

- Thin and lightweight at 38mm thick, 96kg/m³ density
- Contours easily to complex duct designs
- Fully foil encapsulated for fast and clean installation
- Contains 1200°C rated fibre
- Good sound absorption
- A1 Reaction to Fire Classification in accordance with EN 13501-1

FireMaster[®] FastWrap XL



PHYSICAL CHARACTERISTICS

Product	Thickness (mm)	Roll Size		roll/ Ctn.	Wt/ Ctn. (kg)
		Length (mm)	Width (mm)		
FastWrapXL	38	4880	610	1	12,6
	38	4880	1220	1	25,1
	38	7620	610	1	19,6
	38	7620	1220	1	39,2

Storage

FireMaster[®] FastWrap XL should be stored in a dry warehouse environment on pallets. Pallets should not be stacked.

The values given herein are typical values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Therefore, the data contained herein should not be used for specification purposes. Check with your Thermal Ceramics office to obtain current information.