





Cubmitted Date: NEO1011D220V4 ALL		Innovative Ductless Mini Split Solution 18,000 BTU/H Wall Mounted Heat- Pump System		
Submittal Data: NEO18HP230V1AH				ip System
Job Name		Location	Date	
Purchaser		Engineer		_
Submitted To		For Reference	Approval	Construction
Unit Designation		Schedule No.		
GENERAL FEATURES				
-Compact and Quiet Design				
-Easy to read display			Garce	
- Multi speed fan			o ⊕ 88 ⊕ A	1
-Swing Louver				
-Wireless Remote Controllers			1	
-Power Failure Recovery				
-I-Feel Temperature Sensing		2752		
-Limited 5 yr. Parts Warranty		(Sold Separa	te)	1
System Rati	Physical Specifications			
Cooling*	r nysical specifications			
Rated Capacity	18,000 BTU/H	Unit Dimensions (LxH	xD)	37.0 x 11.7 x 7.9-in
Heating at 47° F*		Net Weight		24 LBS
Rated Capacity	19,200 BTU/H			
		Shipping Weight		31 LBS
Sound Pressure Level**				
Cooling (Lo/Hi)	35/49 db(A)	Units Specification & Data		
Heating (Lo/Hi)	35/49 db(A)			
		Air Filter		Polymeric Mesh
Airflow				
Cooling Wet (Lo/Hi)	324/500 CFM	Fan Type		Cross Flow
Heating Dry (Lo/Hi)	354/530 CFM			
		Drain Size (OD)		0.625-in
Electrical Ratings		Refrigerant Piping Data		
Fan Motor		Refrigerant Type		R410A
Output Power	20 W			
FLA	0.3 A	Gas Pipe Size (OD)		1/2-in
Power Supply		Liquid Pipe Size (OD)		1/4-in
Normal Operational Voltage	209/230 V 1 Dbaco 40 Uz	Liquiu Fipe Size (OD)		1/4-111
·	208/230 V, 1 Phase, 60 Hz 187 - 253 V	Connection Method		Flared
Voltage Range MCA	1.0 A	Connection Method		rialeu
Interconnecting Cable Wire Size	1.0 A 14-4 AWG	* Tost conditions are based	d on ΔΗΡΙ 210/240	
interconnecting capie wife Size 14-4 AWG		* Test conditions are based on AHRI 210/240. **Sound Power ratings are per AHRI 270 and AHRI 350		
		Sound Fower fallings are	hei Hilli 510 alia HUKI 330	J
	The state of the s	ALUDI		(Ti)
LIMITED PARTS	RTER RATIONA	AHRICE	ERTIFIED THE Labridirectory.org	くし

DIMENSIONAL SPECIFICATIONS

NEO18HP230V1AH

INDOOR UNIT DIMENSIONS






Liquid Line Valve	1/4-in OD Flared		
Gas Line Valve	1/2-in OD Flared		
Drain Connector	5/8-in OD		

MINIMUM CLEARANCES

Units: inch (mm)



- 1. Recommended Interconnecting Cable Type Stranded Bare Copper Conductors THHN 600V Wire
- 2. Power wiring cable size must comply with applicable national and local codes.
- 3. Test conditions are based on AHRI 210/240.

