



ODORGON™ Spray

FUEL OIL DEODORIZER

DESCRIPTION

ODORGON™ Spray eliminates oil and other industrial odors. The spray covers vertical surfaces as well as hard-to-get-at corners. **ODORGON™ Spray** has a pleasant, mild fragrance that does not linger.

CHARACTERISTICS

- * Deodorizes after spills and leaks
- * Pleasant odor
- * Non flammable
- * Easy to use

APPLICATIONS

ODORGON™ Spray is used to eliminate fuel oil odors from leaking or overfilled tanks, oil burner drippings, in warm air vents and air filters, in garages, grease pits and on equipment.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
68516	14 Oz. Aerosol	12	14	0.447

ODORGON™ Spray FUEL OIL DEODORIZER

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

Spray over oil covered surface. If source of oil odor is not obvious, spray ODORGON™ around general area of odor.

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**WARNING
CONTENTS UNDER PRESSURE
CAUSES EYE IRRITANT
KEEP OUT OF REACH OF CHILDREN**

CONTAINS HEXYLENE GLYCOL AND ALCOHOL

Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. To avoid breathing vapors or mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection or leave the area. Avoid contact with skin or eyes.

FIRST AID: **Skin:** Wash off with soap and water. **Eyes:** Flush with plenty of water. Seek medical attention if irritation persists.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	8.17
Flash Point SETA CC	Negative Flame Extension, (NFPA) Level 1 Aerosol
Color	Clear
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED IN U.S.A. BY
Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com