

Venture 3520CW[®]

Stands up to the Cold

3520CW[®]

- *Temperature range -35° F to +260° F*
- *CW[®] solvent acrylic pressure sensitive adhesive*
- *Specifically designed for sealing sheet metal ducts and metal duct connections*
- *HVAC Industry Leading Foil Tape for Metal Ducts*



VentureTape[®]

800-343-1076
www.venturetape.com

3520CW[®]

Foil Insulation Tape

UL723 Listed

Description

Venture Tape 3520CW[®] COLD WEATHER FOIL is a 2.0-mil (50µm) annealed aluminum foil coated with Venture's CW[®] cold weather solvent acrylic pressure sensitive adhesive. The malleable foil applies easily to both fibrous and sheet metal ducts and conforms to irregular surfaces. Venture Tape 3520CW[®] excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.

Applications:

High performance foil insulation tape is specifically designed for sealing sheet metal ducts and metal duct connections.

Technical Data

	Imperial	Metric
Thickness	3.7 mils	94 µ
Peel Adhesion	100 oz/in	27.7 N/25mm
Shear Strength	>168 Hours	>168 Hours
Tensile Strength	34 lb/in width	151 N/25mm width
Elongation	5%	5%
Temperature Range:	-35° F to +260° F	-12° C to 177° C
Mold Growth	0	0
Roll Size	2, 2 1/2, 3 inches x 50 yds	5.1, 6.4, 7.6 cm x 46m

Important Information:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Users must determine the product suitability for the end use application and assume all risks and liabilities.