





100 CFM/2.0 Sones @ 0.10" SP. 83 CFM @ 0.25 SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 11" x 13%4".

Blower Wheel

One piece polymeric centrifugal blower wheel, $5^{7}/_{32}$ " diameter, $2^{29}/_{32}$ " wide, with 30 paddles.

Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, suitable for continuous operation. Rated 120 volts, 60 bz

Fan Housing

23 gauge galvanized steel housing. Dimensions: $10^{7}/_{8}$ " x $9^{3}/_{8}$ " x $7^{7}/_{8}$ ".

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 100 sq. ft. For other rooms up to 125 sq. ft.


• Electrical Connections

1/2" electrical knockouts provided.

• Single Pack Shipping Info

Box Dim Box Dim: 15¹⁵/₁₆" x 14⁵/₁₆" x 9⁷/₈" UPC: 0-8316221012-8

Shipping Weight: 12 lbs.



133/4"

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

The housing will mount in ceilings with at least 8" of clearence and through drywall thickness up to 3/4", with a rough-in opening of 11/1/8" x 9/18". The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

EXPANDED PERFORMANCE											
								Sones	Fan Speed	Maximum	
	Static Pressure (inches of w.g.)							@ .1 SP	RPM	Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	104	102	100	99	98	95	83	2.0	1106	26.4	0.3

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN Number	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	
1										







U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048 Canada: Brampton, Ontario Tel: 905-456-2033 Fax: (905) 456-1015

Specifications subject to change without notice.

Updated 2-18