

# G1 Single™


SINGLE CYLINDER RECOVERY

## Economical Standard Duty

- Ductless Splits
- PTACs
- Heat Pumps
- Vending
- Easy to use, ideal for residential and appliance recovery jobs
- Comparable recovery rates to larger machines, without the bulk and hassle
- Permanently-lubricated crankcase is isolated from refrigerant, eliminating bearing contamination
- No purge cycle required



High Speed/High Pressure Turbine Fan - Over 600cfm



Modular Construction for Easy Repair

Permanently Lubricated Heavy Duty Crankcase Isolated From Refrigerant

**Pumps R410a Liquid/Vapor**

**Flip Over for → G5 Twin**  
CYLINDER / CONDENSER

### Dimensions and Power

Length	11.38 in.	289 mm
Height	10.30 in.	262 mm
Width	9.40 in.	239 mm
Weight	24 Lbs.	11 Kgs.
Power	115 VAC, 60 Hz, 10 Amps Int'l: 230 VAC, 50 Hz, 5 Amps	

### G1 Single Recovery Rates

Refrigerant	Push-Pull	Liquid	Vapor
R-134a	9.44 lb/min 4.28 kg/min	5.20 lb/min 2.36 kg/min	0.22 lb/min 0.10 kg/min
R-22	10.80 lb/min 4.90 lb/min	8.55 lb/min 3.88 kg/min	0.26 lb/min 0.12 kg/min
R-407c	11.33 lb/min 5.14 kg/min	5.84 lb/min 2.65 kg/min	0.31 lb/min 0.14 kg/min
R-410a	12.17 lb/min 5.52 kg/min	4.32 lb/min 1.96 kg/min	0.26 lb/min 0.12 kg/min



**Only 22 lbs.!**

For More Information Visit:  
[www.AppionInc.com](http://www.AppionInc.com)