



# Safety Data Sheet

## BOSS® 357 Painters Latex Caulk

### Section 1. Identification

Product Identifier BOSS® 357 Painters Latex Caulk  
Synonyms 35701; 03384WH10; C39030WH  
Manufacturer Stock Numbers 03384WH10; C39030WH

Recommended use Refer to Technical Information  
Uses advised against Refer to Technical Information

Manufacturer Contact  
Address

Soudal Accumetric  
350 Ring Road  
Elizabethtown, KY, 42701  
USA

Phone  
(270) 769-3385

Emergency Phone  
(800) 424-9300  
CHEMTREC

Fax  
(270) 765-2412

### Section 2. Hazards Identification

Classification N/A  
Signal Word  
Pictogram  
Hazard Statements N/A  
Precautionary Statements  
Response N/A  
Prevention N/A  
Storage N/A

Disposal N/A  
General If medical advice is needed, have product container or label at hand  
Keep out of reach of children  
Read label before use

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Additional Information While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
27138-31-4	Dipropylene glycol dibenzoate	1% - 5%
13463-67-7	Titanium Dioxide	1% - 5%
64742-46-7	Distillates (petroleum), hydrotreated middle	1% - 5%
7632-00-0	Sodium Nitrite	0.1% - Max

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Ingestion No first aid should be needed.  
Inhalation Remove to fresh air. If symptoms persist, obtain appropriate medical attention.  
Skin Contact Wash affected area with soap and water.  
Eye Contact Rinse with water for 15 minutes. Obtain medical attention.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog  
Unsuitable Extinguishing Media None known  
Flammability Limits in Air Lower: 0.9% by volume  
Upper: 15.3% by volume  
Special Fire Fighting Procedures Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.  
Unusual Fire or Explosion Hazards Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.

## Section 6. Accidental Release Measures

Steps to be taken in case of spill or release      Restrict area to only those personnel needed. Major spills should be collected for disposal. Minor spills may be flushed to sewer if permitted by state, federal and local regulations.

## Section 7. Handling and Storage

Storage      Store in a cool dry place. Protect from freezing and excessive heat.  
Handling      Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Dipropylene glycol dibenzoate	N/A	N/A	N/A
	Titanium Dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	N/A
	Distillates (petroleum), hydrotreated middle	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Sodium Nitrite	N/A	N/A	N/A
Personal Protective Equipment	Goggles, Gloves			
Skin Protection	Impervious gloves are suggested.			
Eye Protection	Safety goggles or glasses with side shields are recommended.			
Respiratory protection	No respiratory protection should be needed with good local ventilation.			
Ventilation	Local exhaust ventilation is recommended to maintain vapor level below TLV.			

## Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Refer to product label
Odor	Slight
Odor Threshold	N/A
Solubility	Dilutable in wet stage
Partition coefficient Water/n-octanol	N/A
VOC%	8.6 g/L
Viscosity	750,000 cPs
Specific Gravity	1.72

Density lbs/Gal	14.3541
Pounds per Cubic Foot	107.37609
Flash Point	Not determined
FP Method	N/A
pH	8
Melting Point	0C
Boiling Point	100C
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Slower than n-Butyl Acetate
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not Determined
Vapor Density	Lighter than air

Note The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

## Section 10. Stability and Reactivity

Chemical Stability Stable  
Materials to Avoid / Incompatibility None known  
Hazardous polymerization Will not occur

## Section 11. Toxicological Information

Component Toxicology Information No known applicable information.  
Special Hazard Information on Components No known applicable information.

## Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants Complete information is not yet available.  
Environmental Effects Complete information is not yet available.

## Section 13. Disposal

Waste Disposal Method	<p>We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.</p> <p>This product is not known to be regulated under RCRA regulations. Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.</p>
-----------------------	--

## Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.

## Section 15. Regulatory Information

TSCA Status	<p>All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.</p> <p>The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.</p>
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 312 Hazard Class	<p>Acute: Yes</p> <p>Chronic: No</p> <p>Fire: No</p> <p>Pressure: No</p> <p>Reactive: No</p>
SARA Title III Section 313 Toxic Chemicals	None present or none present in regulated quantities.
California Prop 65	<p>WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></p>

## Section 16. Other Information

Revision Date

6/1/2018

Disclaimer

The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.