

Builder's Best, Inc. 201 Broiles Drive Jacksonville, TX 75766 888-368-7233 fax: 800-259-8368 www.BuildersBest.com

V330 FLEXIBLE PIPE, ONE END CRIMPED



- DESCRIPTION
 Non-insulated general purpose venting duct for low and medium operating pressures
- Non-combustible flexible metal duct made of corrugated aluminum with water-tight continuous lockseams
- Class 0

PRODUCT SPECIFICATIONS

- 8' lengths
- 3", 4", 5", 7", 8", 9", 10", and 12" diameters
- Compressed to 24"
- One end crimped, one end plain
- Thicker wall than V320

PART NUMBERS

Diameter	Length	Part #	Qty	Package
3"	8'	011489	20	Bulk
4"	8'	011491	12	Bulk
5"	8'	011493	6	Bulk
6"	8'	110317	4	Bulk
7"	8'	110319	4	Bulk
8"	8'	110320	4	Bulk
9"	8'	110322	4	Bulk
10"	8'	110323	4	Bulk
12"	8'	110246	4	Bulk

PERFORMANCE DATA

• Recommended Operating Pressure:


Positive: 6" WC max Negative: 6" WC max


Maximum velocity: 5.000 FPM

Operating Temp. Range:-100°F to +430°F


Flame Speed Smoke Developed 0

INSTALLATION: Air duct connections and joins shall be made per installation instructions outlined by Builder's Best.(Installation instructions are





AIRFIOW





LABELS



WARRANTY

Manufacturer assumes no responsibility for failure due to improper installation. All specifications and designs are subject to change without notice and without incurring liability.

WARRANTY EXCLUSION AND DISCLAIMER Seller specifically excludes, and hereby disclaims any express representation or express warranty of any kind with respect to the goods ordered hereunder. All implied warranties, including without limitation merchantability or fitness for a particular purpose or arising from a course of dealing or usage or trade shall expire and cease 45 days after date of delivery. Seller shall not be liable to buyer or any third party for any special, secondary, incidental, or consequential damages however arising. Nothing in this provision shall invalidate or restrict any right or remedy otherwise available under state or federal law. Materials and specifications subject to change without notice.