

# 8" Coupler 38

## CONTACT

Office: 888.973.7600

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317


[www.clward.com](http://www.clward.com)

## Detail

- Galvanized Steel (ASTM A653 and A924)
- G-60 Galvanized Coating (ASTM A653 and ASTM 90)
- Available in Specialty Metals:
  - Aluminum (ASTM B209 Alloy 3003 Temper H14)
  - 304 Stainless Steel (ASTM A480 2B Finish)
- Pressure Rating: Designed per SMACNA Third Edition 2005 Section 4.8 Figure 4-6 Brand Connections
- Quality 3/8" solid rod damper
- Heavy duty 20 gauge damper blade
- Low leakage damper hardware
- Available with the Locking Rossi™ handle hardware
- Joints are sealed with a "Zero" VOC integral gasket for energy efficiency
- Available with 1.5" and 2.0" stand-offs
- G-90 galvanized steel available



## Profile



NON-DAMPED COUPLERS ARE SUPPLIED  
w/ 3/8" KNOCK-OUTS. DAMPERED COUPLERS  
ARE SUPPLIED w/ 24 Ga. DAMPER BLADES

## Packaging

Product Availability			
Item Code	Description	Quantity	
		Carton	Skid
8COS24GA26DCS	4" Coupler 38	10	280
8COS26GA26DCS	6" Coupler 38	12	192
8COS28GA26DCS	8" Coupler 38	12	192
8COS210GA26DCS	10" Coupler 38	12	120
8COS212GA26DCS	12" Coupler 38	12	120
8COS214GA26DCS	14" Coupler 38	6	84
8COS216GA26DCS	16" Coupler 38	6	54
8COS218GA24DCS	18 Coupler 38		
8COS220GA24DCS	20 Coupler 38		

NOTE: 24 or 26 designates gauge of fitting

