

Duct Liner Adhesive

Qualifies for LEED Credit EQ 4.1

Detail

Premium grade duct liner adhesive.

- Water Based
- UL Classified
- Fast Dry Time
- Exceptional Coverage
- Water Resistant
- Cleans with soap and water or mineral spirits
- Excellent Tack
- Base: Synthetic Latex
- Color: Black
- Solvent: Water
- Weight per Gallon: 9.5 ± 0.5 lbs.
- Solids: 44 ± 2%
- Viscosity: 6,500 CP ± 1,000 CP
- Application Temp: 40°F to 90°F
- Storage Temp: 40°F to 90°F
- Dry Time: 10-20 minutes, depending on temperature, humidity, and application thickness
- Flammability: None
- Flash Point: No flash to boiling
- Coverage: Approximatley 500 sq.ft./gal., depending on application technique
- Freeze Thaw Stability: 5 cycles
- Shelf Life: (Unopened containers) 1 year
- Flame Spread: 0
- Smoke Developed: 0
- Meets ASTM C 916 Type II
- Meets NFPA 90A & 90B
- LEED Compliant



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

Item	Description	Packaging	Weight
DLADHESIVE5	Duct Liner Adhesive - Black 5 gal pail	Each	46 lbs/pail
DLADHESIVE54	Duct Liner Adhesive - Black 54 gal drum	Each	555 lbs/drum
DLADHESIVE5W	Duct Liner Adhesive - White 5 gal pail	Each	46 lbs/pail
DLADHESIVE54W	Duct Liner Adhesive - White 54 gal drum	Each	555 lbs/drum