

HETO 38

A high efficiency take-off for square to round duct connections

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Detail

- Tapered boot design for improved fit on duct
- Galvanized Steel (ASTM A653 and A924)
- G-60 Galvanized Coating (ASTM A653 and ASTM 90)
- Available in Specialty Metals:
 - Aluminum (ASTM B209 Alloy 3003 Temper H14)
 - 304 Stainless Steel (ASTM A480 2B Finish)
- Pressure Rating: Designed per SMACNA Third Edition 2005 Section 4.8 Figure 4-6 Brand Connections
- Meets SMACNA Leakage Class 3 requirements
- Quality 3/8" solid rod damper
- Heavy duty 20 gauge damper blade
- Available with the Locking Rossi™ handle hardware
- Joints are sealed with a "Zero" VOC integral gasket for energy efficiency
- High density double sided neoprene gasket
- Pre-punched holes in base for easy fastening
- Low height allows use in confined areas
- Available with 1.5" and 2.0" stand-offs
- Available in 24 and 26 gauge G-60 galvanized steel
- Gasket is double sided adhesive polyethylene, 1/8" x 1"
- Optional damper handle placement

Profile

