



DAIKIN *ENTRA*

SINGLE ZONE WALL-MOUNTED HEAT PUMP



Elegant and stylish wall-mounted unit



AN IDEAL SOLUTIONS FOR:

- » An ideal solution to noisy and inefficient window or through-the-wall AC units.

FEATURES AND BENEFITS:

- » **Energy Efficient** – Up to 18.0 SEER2, Up to 8.5 HSPF2, Up to 9.8 EER2
- » **Heating Range:** 5° - 65°F.
- » **Cooling Range:** 50° - 115°F.
- » **49 ft.** pre-charged refrigerant length.
- » **Renovations**, remodeling and new construction.
- » Sun rooms, basements, attics, garages, hot or cold spaces, and more.
- » **Compatible** with Daikin *ONE* smart thermostats.
- » **Rooms where floor space comes at a premium** or is not available for other application.
- » **Ceiling void or attic** does not allow for a viable duct run option.
- » **Outstanding 10-Year Parts Limited Warranty***.
- » **Available in 9K to 24K** Btu capacities.



* Complete warranty available from your local dealer or at www.daikincomfort.com. To receive 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. The duration of warranty coverage may depend on the state in which you reside. Some states and provinces do not allow warranty coverage to be conditioned on registration. For a list of states and provinces that do not allow warranty coverage to be conditioned on registration, please visit www.daikincomfort.com/warranty-information or, to request a paper copy of this information, please call us at 1-855-502-3903. Other limitations and exclusions apply, refer to complete warranty details for full list of limitations and exclusions.

App Store® is a registered trademark of Apple Inc.
Google Play and the Google Play logo are trademarks of Google LLC.

INVERTER

R32



Blue Fin Protection.



Auto-Restart.



Econo Mode.

Wi-Fi Capable + App Connectivity



YEAR-ROUND HEAT PUMP COMFORT:

Cooling Operation



Heating Operation



SPECIFICATIONS

Heat Pump Specifications

Unit Size	Indoor Unit Model # / Dimensions (H x W x D)	Outdoor Unit Model # / Dimensions (H x W x D)	Efficiency Rating	Lowest Sound Level (dB(A))		Weight (lbs)		AHRI #
				Indoor*	Outdoor	Indoor	Outdoor	
9,000	FTXC09BVJU9	RXC09BVJU9	18.0 SEER2 / 9.8 EER2 / 8.5 HSPF2 / 1.8 COP	21	49	17	55.1	218461778
	11-1/4 x 30-5/8 x 8-3/4	21-7/8 x 26-5/8 x 11-1/4						
12,000	FTXC12BVJU9	RXC12BVJU9	18.0 SEER2 / 8.4 EER2 / 8.5 HSPF2 / 1.8 COP	21	50	17	55.1	218461779
	11-1/4 x 30-5/8 x 8-3/4	21-7/8 x 26-5/8 x 11-1/4						
18,000	FTXC18BVJU9	RXC18BVJU9	18.0 SEER2 / 7.7 EER2 / 8.5 HSPF2 / 1.8 COP	21	54	19.8	99.2	2184617870
	11-1/4 x 30-5/8 x 8-3/4	29-1/2 x 34-1/4 x 12-5/8						
24,000	FTXC24BVJU9	RXC24BVJU9	18.0 SEER2 / 9.2 EER2 / 8.5 HSPF2 / 1.8 COP	35	54	27.6	108.0	218461781
	11-5/8 x 39-3/8 x 10-3/8	29-1/2 x 34 1/4 x 12-5/8						

*When quiet operation is engaged



BUILD YOUR SYSTEM | DISCOVER REBATES | FIND A CONTRACTOR | LEARN MORE ABOUT DAIKIN:

www.daikincomfort.com



ADDITIONAL INFORMATION

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer.