



## Submittal Data Sheet

1.25-Ton Wall Mounted Unit

FTXG15HVJURXG15HVJU

### FEATURES

- Low ambient heating operation down to -4°F
- Dehumidifying to a preset relative setting
- Integrated air cleaner for advanced filtration for allergens, odors, and bacteria
- 12 year limited parts and compressor warranty with online registration

### BENEFITS

- Compact design

### INDOOR UNIT



### OUTDOOR UNIT





## Submittal Data Sheet

1.25-Ton Wall Mounted Unit

FTXG15HVJURXG15HVJU

### SYSTEM PERFORMANCE

Indoor Unit Model No.	FTXG15HVJU	Indoor Unit Name:	FTXG15HVJU
Outdoor Unit Model No.	RXG15HVJU	Outdoor Unit Name:	RXG15HVJU
Rated Cooling Capacity (Btu/hr):	15,000	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Sensible Capacity (Btu/hr):	11,580	Rated Piping Length(ft):	
Max/Min Cooling Capacity (Btu/hr):	18,000 / 5,300	Rated Height Difference (ft):	26.00
Cooling Input Power (kW):	1.190	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
SEER (Non-Ducted/Ducted):	21.00 /	HSPF (Non-Ducted/Ducted):	10.0 /
EER (Non-Ducted/Ducted):	12.90 /	Heating COP (Non-Ducted/Ducted):	4.0 /
Rated Heating Capacity (Btu/hr):	18,000		
Max/Min Heating Capacity (Btu/hr):	21,200 / 4,400		
Heating Input Power (kW):	1.36		

### SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	14 - 109
Holding Refrigerant Charge (lbs):	3.1	Heating Operation Range (°F WB):	4 - 75
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (°F DB):	14 - 109
Max. Pipe Length (Total) (ft):	33	Heating Range w/Baffle (°F WB):	4 - 75
Max Height Separation (Ind to Ind ft):	26		


# Submittal Data Sheet

1.25-Ton Wall Mounted Unit  
FTXG15HVJURXG15HVJU

**INDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L) (CFM):	487/371/258
Power Supply Connections:	L1, L2, Ground	Moisture Removal (Gal/hr):	5.9
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	3/8
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	12 x 35-1/32 x 8-7/32	Condensate Connection (inch):	11/16
Panel (HxWxD) (in):		Sound Pressure (H/M) (dBA):	44/29
Net Weight (lb):	31	Sound Power Level (dBA):	
Panel Weight (lb):		Ext. Static Pressure (Rated/Max) (inWg):	0.00 / 0.00

## DIMENSIONAL DRAWING - INDOOR UNIT



3D061002

# Submittal Data Sheet


1.25-Ton Wall Mounted Unit

FTXG15HVJURXG15HVJU

## OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Type:	Inverter
Power Supply Connections:	L1, L2, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	14.50	Airflow Rate (H) (CFM):	1,262
Max Overcurrent Protection (MOP) (A):		Gas Pipe Connection (inch):	3/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):	4.6	Sound Pressure (H) (dBA):	50
Dimensions (HxWxD) (in):	22-3/8 x 31-9/32 x 11-7/32	Sound Power Level (dBA):	
Net Weight (lb):	99		

## DIMENSIONAL DRAWING - OUTDOOR UNIT



3D0626