



Submittal Data Sheet

2.0-Ton Wall Mounted Unit

FTXN24KVJURXN24KEVJU5

FEATURES

- Low ambient heat operation down to 0° F
- Titanium apatite photocatalytic air purification filter (option)
- 10 year limited parts and compressor warranty with online registration

BENEFITS

- Quiet operation

INDOOR UNIT



OUTDOOR UNIT





Submittal Data Sheet

2.0-Ton Wall Mounted Unit

FTXN24KVJURXN24KEVJU5

SYSTEM PERFORMANCE

Indoor Unit Model No.	FTXN24KVJU	Indoor Unit Name:	Mini-Split IDU
Outdoor Unit Model No.	RXN24KEVJU5	Outdoor Unit Name:	20 SEER, Heat Pump, ODU k(e) Series, 2 Ton
Rated Cooling Capacity (Btu/hr):	22,000	Rated Cooling Conditions:	Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75
Sensible Capacity (Btu/hr):	14,370	Rated Piping Length(ft):	25
Max/Min Cooling Capacity (Btu/hr):	22,000 / 7,500	Rated Height Difference (ft):	65.60
Cooling Input Power (kW):	3.000	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
SEER (Non-Ducted/Ducted):	/		
EER (Non-Ducted/Ducted):	/		
Rated Heating Capacity (Btu/hr):	24,000		
Max/Min Heating Capacity (Btu/hr):	25,400 / 7,500		
Heating Input Power (kW):	2.90		

SYSTEM DETAILS

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	14 - 115
Holding Refrigerant Charge (lbs):	3.2	Heating Operation Range (°F WB):	5 - 77
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	66
Pre-charge Piping (Length) (ft):	33	Cooling Range w/Baffle (°F DB):	- 115
Max. Pipe Length (Total) (ft):	98	Heating Range w/Baffle (°F WB):	5 - 77
Max Height Separation (Ind to Ind ft):	66		

Submittal Data Sheet


2.0-Ton Wall Mounted Unit

FTXN24KVJURXN24KEVJU5

INDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Airflow Rate (H/M/L/SL) (CFM):	572/480/403/360
Power Supply Connections:	See Outdoor Unit for Electrical Specs	Moisture Removal (Gal/hr):	
Min. Circuit Amps MCA (A):		Gas Pipe Connection (inch):	1/2
Max Overcurrent Protection (MOP) (A):		Liquid Pipe Connection (inch):	1/4
Dimensions (HxWxD) (in):	11-7/16 x 41-5/16 x 9-3/8	Condensate Connection (inch):	11/16
Net Weight (lb):	26.5	Sound Pressure (H/M) (dBA):	46/37
Ext. Static Pressure (Rated/Max) (inWg):	0 /	Sound Power Level (dBA):	

DIMENSIONAL DRAWING - INDOOR UNIT





Submittal Data Sheet


2.0-Ton Wall Mounted Unit

FTXN24KVJURXN24KEVJU5

OUTDOOR UNIT DETAILS

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Stage:	
Power Supply Connections:	L1, L2, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	15.5	Airflow Rate (H) (CFM):	1752
Max Overcurrent Protection (MOP) (A):	20	Gas Pipe Connection (inch):	1/2
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):	12	Sound Pressure (H) (dBA):	54
Dimensions (HxWxD) (in):	23-7/16 x 31-5/16 x 11-13/16	Sound Power Level (dBA):	68
Net Weight (lb):	93		

DIMENSIONAL DRAWING - OUTDOOR UNIT



UNIT=INCH(mm)