Job Name:	
Tag#	



Submittal Data Sheet

FTXS24LVJU / RXS24LVJU

2-Ton Wall Mounted Heat Pump System







Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Indoor Specifications

	Cooling			Heating	
Airflow Rate (cfm)	Н		М	Н	M
	643		494	699	572
	L		SL	L	SL
	350		328	445	403
Sound (dBA) H / M / L / SL	51 / 44 / 37 / 34		37 / 34	48 / 42 /	/ 37 / 34
Dimensions (H \times W \times D) (in)		13-3/8 × 41-5/16 × 9-3/4			
Weight (Lbs)		31			

Outdoor Specifications

•					
Compressor		Hermetically Sealed Swing Type			
Refrigerant		R-410A			
Refrigerant Oil		PVE (FVC50K)			
	Cooling		Heating		
Airflow Rate (cfm)	Н		1,924	Н	1,854
	L		1,624	L	1,624
Sound Power Level (dBA)		66			
Dimensions (H × W × D) (in)		30-5/16 × 35-7/16 × 12-5/8			
Weight (Lbs)		159			

Efficiency

Cooling		Hea	ting
SEER	20.0	HSPF	10.6
EER	12.5	СОР	3.37

Performance

Cooling (Btu/hr)			
Rated (Min/Max)	21,400 (7,800 / 21,500)		
Sensible @ AHRI	16,880		
Moisture Removal gal/h	1.2		
Standard Operating Range	50°F – 115°F		
Extended Operating Range*	0°F – 115°F		

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB

Outdoor: 95°F DB/75°F WB

*With field settings and wind baffle

Heating (Btu/hr)			
1:@ 47° Rated (Min/Max) 25,400 (7,800 / 25,400)			
2: @ 17° Rated	16,400		
3: @ 5° Max	11,340		
Operating Range	5°F – 65°F		

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB

Outdoor: 47°F DB/43°F WB

2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB

Outdoor: 17°F DB/15°F WB

3: Rated Heating Conditions: Indoor: 70°F DB/60°F WB

Outdoor: 5°F DB/5°F WB

Electrical

	208/60/1	230/60/1
System MCA	17.50	17.50
System MFA	20	20
Compressor RLA	7.9	7.1
Outdoor fan motor FLA	.32	.32
Outdoor fan motor W	66	66
Indoor fan motor FLA	.57	.57
Indoor fan motor W	48	48

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)
RLA: Rated load amps (A)
W: Fan motor rated output (W)

Piping

Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.6
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.21


Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Creation Date: July 2017 Page 1 of 4

FTXS24LVJU Dimensional Data






Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Creation Date: July 2017 Page 2 of 4

RXS24LVJU Dimensional Data





Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Creation Date: July 2017 Page 3 of 4

Optional Accessories



	Indoor Unit			
Included	Part Number	Description		
	BRP072A43	Wireless Interface Adapter		
	BRC944B2-A08	Wired Remote Controller		
	BRCW901A08	Wired Remote Controller Cord - 3m		
	DACA-BRCW901P10	Remote Controller Cable, Plenum Rated, 10 ft		
	DACA-BRCW901P25	Remote Controller Cable, Plenum Rated, 25 ft		
	DACA-TS1-1	Daikin ENVi Intelligent Thermostat Kit		
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)		
	DACA-CP4-1	External Condensate Pump		
	KRP928BB2S	Interface Adaptor for DIII-NET		

	Outdoor Unit			
Included	Part Number	Description		
	DACA-WB-3	Powder-Coated Wall-Mounted Bracket		
	KEH041A43 Drain Pan Heater RXS24LV			
	KKP937A4	Drain Plug for OD Unit		
	KPW945A4	Low Ambient Wind Baffle / Air Adjustment Grille (15/18/24 MBH)		