

INSULFLEX

INSULATED FLEXIBLE DUCT CONNECTOR

Pat. No. 4183557

THE **ONLY** INSULATED FLEXIBLE DUCT CONNECTOR

HIGHLIGHTS

• Insulated • 4.2 R Value • Quality Construction • Economically Priced

Energy Efficient, Superior Construction and Economically Priced.

New Advanced INSULFLEX insulated flexible duct connector completes the "insulated" in insulated duct work. INSULFLEX featuring an "R" value of 4.2 with 25% thicker insulation, is a non-porous product that eliminates air leakage.

When excellence is combined with state-of-the-art HVAC technology, the result is a product of true distinction. **New Advanced INSULFLEX** is the obvious choice for totally efficient insulated duct work.

Specifications

FABRIC	FIBERGLASS INSULATION
<ul style="list-style-type: none"> Flame Resistance - passes California Fire Marshal F102.4 on Flame Retardency Total Fabric Thickness - .022 Approx. Thread Count - 28 x 14 Tensile Strength: Warp - 70 lbs. per inch Fill - 70 lbs. per inch Tear Strength: Warp - 8 lbs. per inch Fill - 11 lbs. per inch Adhesion - 30 lbs./2" Coating - Vinyl Heat Resistance: Continuous - 180° Intermittent - 200° Waterproof Air Tight Resistance to grease, oil, gasoline & acid 	<ul style="list-style-type: none"> Thickness: Nominal 1" Density: 1.34 lbs./cu.ft. (28kg/m³) Designed to meet NFPA-90A "R" Value: 4.2
	STEEL
	<ul style="list-style-type: none"> Thickness: 28 Gauge Coating: Galvanized Steel Meets ASTM-A-525-G60

Ordering Information

ITEM NO.	DESCRIPTION	APPROX. DIM. (IN.)	APPROX. LBS.
10173	IDC-343 INSULFLEX Shipped in 100' Rolls	29 x 29 x 10	65

Duro Dyne East Division, Bay Shore, NY	631-249-9000	Fax: 631-249-8346
Duro Dyne Midwest Division, Fairfield, OH	513-870-6000	Fax: 513-870-6005
Duro Dyne West Division, Santa Fe Springs, CA	562-926-1774	Fax: 562-926-5778
Duro Dyne Canada, Lachine, Quebec, Canada	514-422-9760	Fax: 514-636-0328
www.durodyne.com E-mail: durodyne@durodyne.com		

**DURO
DYNE**®

©2009 Duro Dyne Corporation
Printed in USA 07/2009
BC010400