SUBMITTAL RECORD	
JOB	DURO
LOCATION	DUNU
SUBMITTED TO	
SUBMITTAL PREPARED BY	DVNE
APPROVED BY	

## Submittal Form VDS, SVDS, NS Hanging Strap

Duro Dyne provides Hanging Strap fabrics that are waterproof, grease, oil & acid resistant, and have low smoke & flame development. For maximum strength: put the two ends together and fold it over before securing to the ceiling or joist.







	VINYL DURO STRAP	NOVA STRAP	
FLAME SPREAD & SMOKE DEVELOPMENT:	NFPA Class A* UBC Class 1*	Less Than 25 / Less Than 50 ASTME 84	
TENSILE STRENGTH:	Warp-70 lbs./In. Fill-70 lbs./In	Warp-70 lbs./In.; Fill-70 lbs./In	
HEAT RESISTANCE:	200° F	200° F	
TEAR STRENGTH:	Warp- 8 lbs./In. Fill-11 lbs./In	N/A	
FABRIC:	Black vinyl coated polyester fill	Black Woven Polypropylene	
TOTAL FABRIC THICKNESS:	.022" Approx.	.025" Approx.	
QUANTITY PER CARTON:	10 rolls (Conveniently packaged in a dispenser box with cutting blade)  24 rolls per box		
ADDITIONAL INFO:	*Product Meets NFPA Class A and UBC Class 1 characteristics of flame spread less than 25 and smoke development less than 50 when utilizing test method ASTM E-84.	Resistant to Grease, Oil, Gasoline and Acid.	

HANGING STRAP				
ITEM#	MODEL	DESCRIPTION	SIZE	
10190	VDS200	Vinyl Duro Strap	1-1/2" x 200'	
10179	SVDS300	Single Sided Vinyl Duro Strap	1-1/2" x 300'	
10180	NS300	Nova Strap	1-3/4" x 300"	

## **Best Installation Practices**

The Air Duct Council recommends supporting flex duct at manufacturers recommended intervals or no greater than 4'. Maximum centerline sag shall be no more than 1/2" per foot. Hanging Strap must be a minimum of 1-1/2" wide. For more information, please visit the Air Duct Council "Supporting Flexible Duct" section 4.6.



