Stainless Steel Flexible Gas Connectors

Complete selection of flexible connectors for gas appliance applications.







Stainless Steel Flexible

Gas Connectors

Applications : Dryers, Boilers, BBQ Grills, Ranges/ Ovens, Furnaces, Fireplaces, Space Heaters, Tankless Water Heaters, Rooftop Units, Manufactured Homes



Availability

Types	 Stainless Steel (Uncoated) Yellow Epoxy Coated Stainless Steel Black Epoxy Coated Stainless Steel 			
Lengths	12", 18", 24", 30", 36", 48", 60", 72"			
Sizes	3/8" OD (1/4" ID)	1/2" OD (3/8" ID)	5/8" OD (1/2" ID)	1" OD (3/4" ID)
Fittings & Valves	1/2" MIP (3/8"Tapped) 1/2" FIP 1/2" FIP Ball Valve 1/2" FIP Angle Valve	3/8" MIP (1/4"Tapped) 3/8" FIP	3/4" MIP (1/2"Tapped) 3/4" FIP 3/4" FIP Ball Valve 3/4" FIP Angle Valve	1" MIP (3/4"Tapped) 1" FIP

Materials

• Tubing: Stainless Steel 304(ASTM A240)

• Fittings : Zinc-Plated Steel S45C

• Coating: Epoxy

Specifications

• Rated Pressure: 0.5 psi

• Rated Operating Temperature : -40°F to 150°F

(-40°C to 65°C)

Certifications & Listings

- ANSI Z21.24 / CSA 6.10 Gas Appliances
- ANSI Z21.69 / CSA 6.16 Movable Gas Appliances
- ANSI Z21.75 / CSA 6.27 Outdoor Gas Appliances & Manufactured Homes
- Commonwealth of Massachusetts Board of State Examiners
- City of New York-MEA #376-92-M



