

Multi-Room Ductless systems

| Submittal Data: CONS | 100HD230V1AF | | /H Mini Floor | | n Ductless systems |
|--|---|---------------|--|----------|-----------------------|
| | JUJHPZJUV IAF | | | | |
| Job Name | | Location | | Date | |
| Purchaser | | Engineer | | | Construction |
| Submitted To | | For | Reference | Approval | |
| Unit Designation | I | Schedule | No. | | |
| GENERAL FEATURES -Quiet Operation -Multi-Speed Fan | | | C. | | J m to |
| -Swing Louvers | | | | | |
| -Wireless Remote Controllers | | | | | |
| -Remote Control Lockout | | 199 | and the second s | | |
| -Limited 5 yr. Parts Warranty | | 1111 | | | |
| | | | | | |
| System Ra | | Physic | al Specificatior | าร | |
| Cooling* | | | | | |
| Rated Capacity | 8,874 BTU/H | Unit Dimen | sions (LxHxD) | | 27.5 x 24.0 x 8.5 -ir |
| | | | | | 700 x 600 x 215-mm |
| Heating* | | | | | |
| Rated Capacity | 9,556 BTU/H | Weight (N | et/Shipping) | | 33/40 LBS |
| Sound Pressure (Hi/Lo)** | | Drain Size (C | (ח(| | 0.67-ir |
| Cooling | 40/25 dbA | | , | | 17-mm |
| Heating | 40/25 dbA | | | | |
| 5 | | | | | |
| Air Flow (max) | | | | | |
| Indoor Fan | 294 CFM | | | | |
| | | | | | |
| | | | | | |
| Electrical F | Refrigerant Piping Data | | | | |
| Fan Motor | | Refrigerant | Type | | R410A |
| Output Power | 30 W | <u> </u> | | | |
| FLA | 0.36 A | Gas Pipe S | Size (OD) | | 3/8-ir |
| | | | 0 | | |
| Power Supply | | Liquid Pipe | Size (OD) | | 1/4-ir |
| Normal Operational Voltage | 208/230 V, 1 Phase, 60 Hz | | | | |
| Voltage Range | 187 - 253 V | Connection | Nethod | | Flared |
| MCA | 1.0 A | | | | |
| Interconnecting Cable Wire Size | 14-4 AWG | + - 1 | , , <u>.</u> | | |
| | | | ns are based on Al | | |
| | **Sound Power ratings are per AHRI 270 and AHRI 350 | | | | |
| RAIDA | AHRI | CERTIFIED THE | | | ED |
| non azone-depleting ruhigerore | | | | | LISTED |

