



GREE				Multi-Roo	m Ductless systems
Submittal Data: CONS	12HP230V1AF	12,000 BT	U/H Mini Floo		
Job Name		Location		Date	
Purchaser		Engineer			
Submitted To		For	Reference	☐ Approval	Construction
Unit Designation		Schedule	No.		
GENERAL FEATURES					
-Quiet Operation -Multi-Speed Fan					J 30
-Swing Louvers					
-Wireless Remote Controllers					
-Remote Control Lockout		1119	3		
-Limited 5 yr. Parts Warranty		In			
System Ra	tings		Physica	al Specificatio	ns
Cooling*					
Rated Capacity	11,946 BTU/H	Unit Dime	nsions (LxHxD)		27.5 x 24.0 x 8.5 -in
Hootines*					700 x 600 x 215-mm
Heating*	12,969 BTU/H	Moight (N	lot/Chinning)		33/40 LBS
Rated Capacity	12,909 610/11	vveignt (iv	let/Shipping)		33/40 LB3
Sound Pressure (Hi/Lo)**		Drain Size (	OD)		0.67-in
Cooling	42/27 dbA	(	,		17-mm
Heating	42/27 dbA				
Air Flow (max)					
Indoor Fan	353 CFM				
indoor rain	555 ST III				
Electrical Ratings		Refrigerant Piping Data			
Fan Motor		Refrigerar	nt Type		R410A
Output Power	30 W				
FLA	0.36 A	Gas Pipe	Size (OD)		3/8-in
Power Supply		Liquid Pip	e Size (OD)		1/4-in
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz				
Voltage Range	187 - 253 V	Connectio	n Method		Flared
MCA	1.0 A				
Interconnecting Cable Wire Size	14-4 AWG			IDI 040/040	
			ons are based on Al		050
			er ratings are per Al-	1KI 2/U and AHRI	350
RATIONA	ALRI	CERTIFIED TO WWw.ahridirectory.org			(ETI)

## 12,000 BTUH MODEL


Model # CONS12HP230V1AF 12,000 BTUH 230V







Back




Dimensions

(mm) (inches)

Α	В	С	Н	
700	215	200	600	
27.6	8.5	7.875	23.6	

Note: Size refrigerant lines based on evaporator port sizes.

## **MINIMUM CLEARANCES**



MINIMUM INDOOR CLEARANCE Inches (mm)

A	В	c	D	
60 (1524)	24 (610)	6(152)	24 (610)	

## Notes

- 1. Recommended Interconnecting Cable Type Stranded Bare Copper Conductors THHN 600V Unshielded Wire
- 2. Power wiring cable size must comply with applicable national and local codes.
- 3. Test conditions are based on AHRI 210/240.

