



GREE				Multi-Roor	n Ductless systems
Submittal Data: CONS	18HP230V1AF	18,000 BT	TU/H Mini Floo	r Console Unit	
Job Name		Location		Date	
Purchaser		Engineer			
Submitted To		For	☐ Reference	☐ Approval	☐ Construction
Unit Designation		Schedule	No.		
GENERAL FEATURES					
-Quiet Operation -Multi-Speed Fan			1		J 20
-Swing Louvers					
-Wireless Remote Controllers					
-Remote Control Lockout		100			
-Limited 5 yr. Parts Warranty		11/11			
			P		
System Ra	itings		Physic	al Specification	าร
Cooling*					
Rated Capacity	18,089 BTU/H	Unit Dime	nsions (LxHxD)		27.5 x 24.0 x 8.5 -in
					700 x 600 x 215-mm
Heating*	40 705 PTI // I	VA / - 1 - 1 - / N	1. (/01.1 1)		22/42 DO
Rated Capacity	19,795 BTU/H	vveignt (r	Net/Shipping)		33/40 LBS
Sound Pressure (Hi/Lo)**		Drain Size (OD)		0.67-in
Cooling	48/32 dbA	\ \	,		17-mm
Heating	48/32 dbA				
<u>-</u>					
Air Flow (max)	200 0511				
Indoor Fan	383 CFM				
Electrical R	Ratings	Refrigerant Piping Data			
Fan Motor		Refrigerar	nt Tyne		R410A
Output Power	30 W	Tonigeral	1 ypo		11410/
FLA	0.36 A	Gas Pipe	Size (OD)		1/2-in
	3.507.1		V · /		
Power Supply		Liquid Pip	e Size (OD)		1/4-in
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz				
Voltage Range	187 - 253 V	Connection	n Method		Flared
MCA	1.0 A				
Interconnecting Cable Wire Size	14-4 AWG				
			ons are based on A		
			er ratings are per Al	HKI 270 and AHRI 3	350
RASTIONAL MARKET	AHRI	CERTIFIED TO NW. ahridirectory.org			(I)

18,000 BTUH MODEL


Model # CONS18HP230V1AF 18,000 BTUH 230V



Front



Back




Dimensions

(mm) (inches)

Α	В	B C H	
700	215	200	600
27.6	8.5	7.875	23.6

Note: Size refrigerant lines based on evaporator port

MINIMUM CLEARANCES



MINIMUM INDOOR CLEARANCE Inches (mm)

A	В	с	D
60 (1524)	24 (610)	6(152)	24 (610)

Notes

- 1. Recommended Interconnecting Cable Type Stranded Bare Copper Conductors THHN 600V Unshielded Wire
- 2. Power wiring cable size must comply with applicable national and local codes.
- 3. Test conditions are based on AHRI 210/240.

