Universal Floor/Ceiling

Our Multi21 Universal Floor/Ceiling indoor units are designed to be suspended from a ceiling or mounted low on a wall. The slender and lightweight design is perfect for restaurants or hallways where wall space is limited.



Features and Benefits:

- ▶ 4-way Discharge Air
- Multi Speed Fan
- ► IR Remote and XK -19 Wired Controller incl.
- ▶ Comfortable Sleep Mode
- ▶ Swing Louver
- ▶ Cleanable Air Filter

- ▶ Dry Coil mode for Anti -Mildew Protection
- ▶ Remote Control Lockout
- ▶ Power Failure Recovery

MODELS		FLR09HP230V1AF	FLR12HP230V1AF	FLR18HP230V1AF	FLR24HP230V1AF	
System Type		Heat Pump				
		SYSTEM PERFORMANCE				
Cooling Capacity (Min-Max)	Btu/h	8,500 (5,460-14,300)	11,900 (6,100-15,300)	17,000 (7,500-24,200)	22,800 (8,200-31,000)	
Heating Capacity (Min-Max)	Btu/h	9,500 (5,100-10,900)	13,100 (6,800-13,600)	18,700 (6,800-22,200)	27,400 (7,500-28,200)	
Airflow (max)	CFM	265/383	265/383	294/559	412/736	
Sound Level (min-max)	dB(A)	36/40	36/40	40/45	44/48	
Dehumidification	pt/hr	1.7	3.0	3.8	5.3	
Unit Dimensions (WxHxD)	in	48.0 x 27.6 x 8.9	48.0 x 27.6 x 8.9	48.0 x 27.6 x 8.9	48.0 x 27.6 x 8.9	
Package Dimensions (WxHxD)	in	53 x 32 x 12.5	53 x 32 x 12.5	53 x 32 x 12.5	53 x 32 x 12.5	
Weight (Net/Gross)	lbs	88.0/110.0	88.0/110.0	88.0/110.0	99.0/118.8	
		INSTALLATION				
Line Set Size (Liquid - Gas)	in	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	3/8 - 5/8	
Limited Warranty		5 Years on Parts				