







Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

## Section 1 - PRODUCT AND COMPANY IDENTIFICATION

#### **Material Name**

Roto-Tack

## **Synonyms**

Water-based Adhesive

## **Chemical Family**

Adhesive

#### **Product Use**

wWater based Adhesive

#### **Restrictions on Use**

For industrial use only.

#### **Manufacturer Information**

Carlisle HVAC Products 900 Hensley Lane Wylie, TX 75098 www.carlislehvac.com

## **Medical Emergency:**

CHEMTREC (USA): (800) 424-9300

MSDS Assistance – 972-442-6545 Technical Assistance – 888-229-2199 Customer Service – 888-229-0199

### Section 2 - HAZARDS IDENTIFICATION

## Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Reproductive Toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure - Category 1 (body, central nervous system, systemic toxicity, eyes)

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (eyes,central nervous system)

## **GHS Label Elements**

### Symbol(s)





Signal Word

Danger

Page 1 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

## **Hazard Statement(s)**

May damage fertility or the unborn child

Causes damage to organs

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

### **Precautionary Statement(s)**

#### **Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Do not eat, drink or smoke when using this product

#### Response

If exposed: Call a POISON CENTER or doctor/physician

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

Specific treatment (see label)

## Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

## **Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

#### Other Hazards

No additional information available.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Mixture	Polymer, ethyl acrylate and methacrylic acid	1-5
Trade Secret	De-foaming agent	0.1-1
7664-41-7	Ammonia	0.1-1
Mixture	Polymer, vinyl acetate and vinyl acrylic	10-30
Trade Secret	Clay compound	0.1-1
1317-65-3	Limestone	1-5
67-56-1	Methanol	1-5

Page 2 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

Trade Secret	Carbamic acid mixture	0.1-1
Mixture	Acrylic polymer emulsion	15-40
Mixture	Fuller's earth	1-5
Mixture	1,2-Benzisothiazolin-3-one mixture	0.1-1

## Section 4 - FIRST AID MEASURES

## **Description of Necessary Measures**

If exposed: Call a POISON CENTER or doctor/physician.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

Wash exposed skin with soap and water. Remove contaminated clothing and wash it before reuse. If skin irritation occurs, get medical advice/attention.

#### Eves

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

#### **Ingestion**

Do NOT induce vomiting. If swallowed, get medical attention.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

### **Most Important Symptoms/Effects**

#### Acute

May cause mild eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to respiratory system, body, central nervous system, systemic toxicity, eyes.

#### **Delayed**

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

### **Note to Physicians**

Contains: ammonia, methanol.

## Section 5 - FIRE FIGHTING MEASURES

### **Extinguishing Media**

## **Suitable Extinguishing Media**

Use carbon dioxide, regular dry chemical, regular foam or water.

Page 3 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

## **Unsuitable Extinguishing Media**

None known.

### **Special Hazards Arising from the Chemical**

Slight fire hazard. Sealed containers may rupture or explode if exposed to heat.

#### **Hazardous Combustion Products**

Oxides of carbon, oxides of nitrogen, hydrocarbons

## **Fire Fighting Measures**

Remove product from area of fire. Stay upwind and keep out of low areas.

## **Special Protective Equipment and Precautions for Firefighters**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

## Section 6 - ACCIDENTAL RELEASE MEASURES

## **Personal Precautions, Protective Equipment and Emergency Procedures**

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

#### **Environmental Precautions**

Avoid release to the environment.

## Section 7 - HANDLING AND STORAGE

## **Precautions for Safe Handling**

This product contains crystalline silica, which is a known carcinogen: Do not grind or sand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN.

## Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Store above 0 C. Store below 45 C. Do not cut, puncture, or weld on or near this container. Avoid contact with incompatible materials.

## **Incompatible Materials**

Strong acids, strong oxidizing agents

Page 4 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack

Product #:308573 -50 gal 308574- 1 gallon

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## **Component Exposure Limits**

	I		
Ammonia	7664-41-7		
ACGIH:	25 ppm TWA 35 ppm STEL		
NIOSH:	25 ppm TWA; 18 mg/m³ TWA	35 ppm STEL; 27 mg/m <sup>3</sup> STEL	
	300 ppm IDLH		
Europe:	20 ppm TWA; 14 mg/m <sup>3</sup> TWA	50 ppm STEL; 36 mg/m <sup>3</sup> STEL	
OSHA (US):	50 ppm TWA; 35 mg/m <sup>3</sup> TWA		
Mexico:	25 ppm TWA LMPE-PPT; 18 mg/m <sup>3</sup> TW	VA LMPE-PPT	
	35 ppm STEL [LMPE-CT]; 27 mg/m <sup>3</sup> ST	TEL [LMPE-CT]	
Clay compound	Trade Secret		
ACGIH:	0.025 mg/m³ TWA respirable fraction		
NIOSH:	0.05 mg/m³ TWA respirable dust 50 mg/m³ IDLH respirable dust		
OSHA (US):	((30)/(%SiO2 + 2) mg/m³ TWA) total dust; ((250)/(%SiO2 + 5) mppcf TWA) respirable fraction; ((10)/(%SiO2 + 2) mg/m³ TWA) respirable fraction		
Mexico:	0.1 mg/m <sup>3</sup> TWA LMPE-PPT respirable fraction		
Limestone	1317-65-3		
NIOSH:	10 mg/m³ TWA total dust; 5 mg/m³ TWA respirable dust		
OSHA (US):	15 mg/m³ TWA total dust; 5 mg/m³ TWA respirable fraction		
Mexico:	10 mg/m³ TWA LMPE-PPT 20 mg/m3 STEL [LMPE-CT]		
Methanol	67-56-1		
ACGIH:	200 ppm TWA	250 ppm STEL	
	Skin - potential significant contribution to	o overall exposure by the cutaneous route	
NIOSH:	200 ppm TWA; 260 mg/m³ TWA 250 ppm STEL; 325 mg/m³ STEL		
	Ī		

Page 5 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

	Potential for dermal absorption
	6000 ppm IDLH
Europe:	200 ppm TWA; 260 mg/m³ TWA
	Possibility of significant uptake through the skin
OSHA (US):	200 ppm TWA; 260 mg/m³ TWA
Mexico:	200 ppm TWA LMPE-PPT; 260 mg/m³ TWA LMPE-PPT
	250 ppm STEL [LMPE-CT]; 310 mg/m <sup>3</sup> STEL [LMPE-CT]
	Skin - potential for cutaneous absorption

## Biological limit value

There are no biological limit values for any of this product's components.

#### **Engineering Controls**

Ensure adequate ventilation. Ensure compliance with applicable exposure limits.

## Individual Protection Measures, such as Personal Protective Equipment

#### **Eve/face protection**

Wear safety glasses or safety goggles, with a faceshield, as appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

#### **Skin Protection**

Wear appropriate work clothing.

## **Respiratory Protection**

A NIOSH approved respirator with a dust, mist, and fume filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits or when symptoms have been observed that are indicative of overexposure.

#### **Glove Recommendations**

Wear appropriate gloves. Recommended material type: Hycron(R), neoprene, nitrile.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	white latex	Physical State	liquid
Odor	Slight,ammonia	Color	white
Odor Threshold	Not available	рН	Slightly acidic
Melting Point	Not available	<b>Boiling Point</b>	100°C (212 °F)
Freezing point	Not available	<b>Evaporation Rate</b>	62 - 66 % volatile
<b>Boiling Point Range</b>	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available

Page 6 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

Lower Explosive Limit	Not available	Decomposition	Not available
<b>Upper Explosive Limit</b>	Not available	Vapor Pressure	17 mmHg (@ 20 °C)
Vapor Density (air=1)	<1	Specific Gravity (water=1)	Not available
Water Solubility	Soluble	Partition coefficient: n-octanol/water	Not available
Viscosity	2000 - 3000 cps	Solubility (Other)	Not available
Density	1.03 (relative)	voc	73 g/L (water excluded)

#### Other Information

No additional information available.

#### Section 10 - STABILITY AND REACTIVITY

#### Reactivity

No reactivity hazard is expected.

### **Chemical Stability**

Stable under normal conditions of use.

## **Possibility of Hazardous Reactions**

Hazardous polymerization will not occur.

## **Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

### **Incompatible Materials**

Strong acids, strong oxidizing agents

### **Hazardous decomposition products**

Oxides of carbon, oxides of nitrogen, hydrocarbons

#### Section 11 - TOXICOLOGICAL INFORMATION

## **Information on Likely Routes of Exposure**

#### Inhalation

May cause respiratory irritation. May cause drowsiness or dizziness.

### **Skin Contact**

May cause mild skin irritation.

#### **Eve Contact**

May cause mild eye irritation.

#### **Ingestion**

Methanol can produce blindness with onset of symptoms being delayed for 18-24 hours.

### **Acute and Chronic Toxicity**

Page 7 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

## Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Polymer, ethyl acrylate and methacrylic acid (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

De-foaming agent (Trade Secret)

Oral LD50 > 2000 mg/kg

Chlorinated paraffins (Trade Secret)

Oral LD50 Rat >4 g/kg

Ammonia (7664-41-7)

Oral LD50 Rat 350 mg/kg

Inhalation LC50 Rat 2000 ppm 4 h

Polymer, vinyl acetate and vinyl acrylic (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rat >2000 mg/kg

Clay compound (Trade Secret)

Oral LD50 Rat 500 mg/kg

Limestone (1317-65-3)

Oral LD50 Rat 6450 mg/kg

Methanol (67-56-1)

Oral LD50 Rat 6200 mg/kg

Inhalation LC50 Rat 22500 ppm 8 h

Carbamic acid mixture (Trade Secret)

Oral LD50 Rat >2000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Inhalation LC50 Rat >2.04 mg/L 4 hr

Acrylic polymer emulsion (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

1,2-Benzisothiazolin-3-one mixture (Mixture)

Oral LD50 Rat 2342 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

Inhalation LC50 Rat 900 mg/m3 4 hr

## **Immediate Effects**

May cause mild eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Causes damage to respiratory system, body, central nervous system, systemic toxicity, eyes.

#### **Delayed Effects**

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: eyes, central nervous system.

#### **Irritation/Corrosivity Data**

May cause respiratory irritation. May cause mild skin irritation. May cause mild eye irritation.

### **Respiratory Sensitization**

No data available.

#### **Dermal Sensitization**

Page 8 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

No data available.

## **Component Carcinogenicity**

Chlorinated paraffins	Trade Secret
IARC:	Monograph 48 [1990] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man)
OSHA:	Present
Clay compound	Trade Secret
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (respirable size)
DFG:	Category 1 (causes cancer in man, alveola fraction)
OSHA:	Present (respirable size)

## **Germ Cell Mutagenicity**

No data available.

## **Tumorigenic Data**

No data available

### **Reproductive Toxicity**

May damage fertility or the unborn child.

## **Specific Target Organ Toxicity - Single Exposure**

Central nervous system, body, systemic toxicity, eyes

## **Specific Target Organ Toxicity - Repeated Exposure**

Central nervous system, eyes

### **Aspiration hazard**

No data available.

## **Medical Conditions Aggravated by Exposure**

No data available.

#### **Additional Data**

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

## Section 12 - ECOLOGICAL INFORMATION

Page 9 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

## **Ecotoxicity**

Avoid release to the environment.

**Component Analysis - Aquatic Toxicity** 

Component Analysis - Aquati	
Polymer, ethyl acrylate and methacrylic acid	Mixture
Fish:	LC50 96 hr Pimephales promelas >1000 mg/L
Invertebrate:	EC50 48 hr Daphnia magna >1000 mg/L
Chlorinated paraffins	Trade Secret
Fish:	LC50 96 h Lepomis macrochirus >300 mg/L [static]; LC50 96 h Oncorhynchus mykiss >0.0109 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 94.5 - 271 mg/L [static]; LC50 96 h Lepomis macrochirus >0.1 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]
Invertebrate:	EC50 48 hr Daphnia magna 0.0059 mg/L
Ammonia	7664-41-7
Fish:	LC50 96 h Cyprinus carpio 0.44 mg/L; LC50 96 h Lepomis macrochirus 0.26 - 4.6 mg/L; LC50 96 h Lepomis macrochirus 1.17 mg/L [flow-through]; LC50 96 h Pimephales promelas 0.73 - 2.35 mg/L; LC50 96 h Pimephales promelas 5.9 mg/L [static]; LC50 96 h Poecilia reticulata >1.5 mg/L; LC50 96 h Poecilia reticulata 1.19 mg/L [static]
Invertebrate:	LC50 48 h Daphnia magna 25.4 mg/L IUCLID
Polymer, vinyl acetate and vinyl acrylic	Mixture
Fish:	LC50 96 hr Oncorhynchis mykiss >1000 mg/L
Invertebrate:	EC50 48 hr Daphnia magna >100 mg/L
Methanol	67-56-1
Fish:	LC50 96 h Pimephales promelas 28200 mg/L [flow-through]; LC50 96 h Pimephales promelas >100 mg/L [static]; LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L [flow-through];

Page 10 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

	LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L [static]; LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L [flow-through]	
1,2-Benzisothiazolin-3-one mixture	Mixture	
Fish:	LC50 96 hr Rainbow trout 21 mg/L [flow-through]	
Invertebrate:	EC50 48 hr Daphnia magna 26 mg/L	

## **Persistence and Degradability**

No information available for the product.

## **Bioaccumulative Potential**

No information available for the product.

## Mobility

No information available for the product.

## **Other Toxicity**

No additional information available.

## Section 13 - DISPOSAL CONSIDERATIONS

### **Disposal Methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 14 - TRANSPORT INFORMATION

## **US DOT Information:**

UN/NA #: Not regulated

### **IATA Information:**

**UN#:** Not regulated

### **TDG Information:**

**UN#:** Not regulated

### **IMDG Information:**

**UN#:** Not regulated

Page 11 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

### Section 15 - REGULATORY INFORMATION

## **U.S. Federal Regulations**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Ammonia	7664-41-7
SARA 302:	500 lb TPQ
SARA 313:	1 % de minimis concentration (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)
CERCLA:	100 lb final RQ; 45.4 kg final RQ
OSHA (safety):	10000 lb TQ anhydrous); 15000 lb TQ solution, >44% Ammonia by weight)
SARA 304:	100 lb EPCRA RQ
Methanol	67-56-1
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ
Carbamic acid mixture	Trade Secret
CERCLA:	10 lb final RQ; 4.54 kg final RQ

## SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: No Pressure: No Reactivity: No

#### **U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Chlorinated paraffins	Trade Secret	No	Yes	No	No	No
Ammonia	7664-41-7	Yes	Yes	Yes	Yes	Yes
Clay compound	Trade Secret	No	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	Yes	Yes
Methanol	67-56-1	Yes	Yes	Yes	Yes	Yes
Carbamic acid mixture	Trade Secret	No	No	No	Yes	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

Page 12 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









Material Name: Roto-Tack

Product #:308573 -50 gal
308574- 1 gallon

WARNING! This product contains a chemical known to the state of California to cause cancer WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Clay compound	Trade Secret
Carc:	carcinogen, 10/1/1988 (airborne particles of respirable size)
Methanol	67-56-1
Repro/Dev. Tox	developmental toxicity, 3/16/2012

## **Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Ammonia	7664-41-7
	1 %
Clay compound	Trade Secret
	1 %
Methanol	67-56-1
	1 %

## **Component Analysis - Inventory**

Polymer, ethyl acrylate and methacrylic acid (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

#### Chlorinated paraffins (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Ammonia (7664-41-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Clay compound (Trade Secret)

Page 13 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17









**Material Name: Roto-Tack** 

Product #:308573 -50 gal 308574- 1 gallon

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Limestone (1317-65-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	NSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Methanol (67-56-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## Carbamic acid mixture (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes

## Fuller's earth (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

## 1,2-Benzisothiazolin-3-one mixture (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

## **Section 16 - OTHER INFORMATION**

## **HMIS Rating**

Health: 2\* Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## **NFPA Ratings**









Material Name: Roto-Tack Product #:308573 -50 gal 308574- 1 gallon

Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Summary of Changes** New SDS: May 22, 2015

## Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

#### **Other Information**

#### **Disclaimer:**

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 15 of 15 Issue date: 2015-05-29 Revision 1.0 Print date: 2016-02-17