



AB-151 Scrim is an all purpose fiberglass ductwork scrim primarily used for temporary fixation of ductwork prior to sealant application. For use with UL 181A-M Listed applications.

### APPLICATION

Temperature	35°F to 110°F (1.7°C to 44°C)
Method	Cut desired length, peel off release liner, apply. Overlap at ends. Rub down with heavy pressure to assure complete contact.
Preparation	Surface must be dry and free of dirt, plus oil and grease.
Clean Up	UN-TACK™ or Solvent (Use safe handling practices.)

### STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C) DO NOT FREEZE
Shelf Life	24 months
Flammability	Non-flammable

### PRECAUTIONS

Surface must be clean and free of moisture, contamination and foreign matter. Do not allow this product to freeze. Do not apply this when rain or freezing temperatures will occur within 36 hours. Do not apply this product where temperatures will exceed 200°F. Keep out of the reach of children. Review MSDS for complete safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.)

**For Industrial Professional Use Only.**

### PART NUMBER

310553 1 Case w/ (18) 3" x 150' Rolls

### TECHNICAL DATA

Average net weight	1.8 (oz./yd <sup>2</sup> )
Minimal Tensile (warp & fill)	70 (lbs./in.)
Thread Count (per inch of width)	Warp threads.....20 Filling threads.....10
Thickness	.005 in.
Packaging	3" x 150'; 18 rolls per case