

## PART NUMBERS

321500	1 5-Gallon Pail
--------	-----------------

## TECHNICAL DATA

Color	Gray
Consistency	Heavy viscous
Base	Synthetic rubber
Solvent	Mineral spirits
Weight per Gallon	9.7 lbs.
Solids Content	86%
Viscosity	Thixotropic
Coverage	1550 linear ft./gal., 1/8 in. bead
Flexibility	Excellent
Time to Test	Immediately
Service Temperature	-30°F to 200°F (-1.1°C to 93.3°C)
Surface Burning*	Flame spread.....0 Smoke developed...5
Water Resistance	Excellent
Mildew Resistance	Excellent
VOC	198 g/l
Pressure Classes	SMACNA 1/2, 1, 2, 3, 4, 6 and 10 inches w.g.
Seal Class	Meets Seal Class A
Packaging	5-gal.
Freeze/Thaw Stability	Excellent

\*When tested in accordance with ASTM E84

## PRECAUTIONS

COMBUSTIBLE. Harmful if swallowed or inhaled. May cause eye irritation. Keep out of the reach of children. Review Material Safety Data Sheet for complete safety information prior to use

**For Industrial Professional Use Only.**

Cold-Seal is a cold-applied, non-hardening, fire-retardant seam sealant for use in rectangular, longitudinal, Pittsburgh™, snap-lock or similar metal duct seams. Cold-Seal will not string, saving equipment cleanup labor. In addition, Cold-Seal resists drying in equipment hoses, avoiding costly replacement.

## APPLICATION

Temperature	35°F to 90°F (1.7°C to 32°C)
Preparation	Surface must be dry and free of dirt, oil and grease.
Rate	Apply 1/8" bead to seams prior to closing
Clean Up	UN-TACK™ or Solvent (Use safe handling practices.)

## STORAGE

Temperature	35°F to 90°F (1.7°C to 32°C)
Shelf Life	One year (unopened)
Flammability	Combustible. Flash Point 150°F (Tcc). Store according to local codes.