Printing date 07.11.2014 Revision: 07.10.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Eco-Perm Coating
- · Article number: 11-02, 11-09
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Mon-Eco Industries, Inc.

5 Joanna Ct.

East Brunswick, NJ 08816 Phone: 732-257-7942



ChemTel Inc.

(800)255-3924, +1 (813)248-0585



SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.



health hazard

Carc. 1A H350 May cause cancer.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T; Toxic

R45-49: May cause cancer. May cause cancer by inhalation.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

(Contd. on page 2)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 1)

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Attapulgite (Palygorskite)

titanium dioxide

Quartz (SiO2)

Petroleum Distillates

chlorothalonil (ISO)

· Hazard statements

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H412.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P281 Use personal protective equipment as required.

P264 Wash thoroughly after handling.

P202 Do not handle until all safety precautions have been read and understood.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Restricted to professional users.

(Contd. on page 3)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 2)

- · Hazard description:
- · WHMIS-symbols:

D2A - Very toxic material causing other toxic effects



· NFPA ratings (scale 0 - 4)



Health = 1Fire = 0Reactivity = 0

· HMIS-ratings (scale 0 - 4)



○ Fire = 0

REACTIVITY Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

HMIS Long Term Health Hazard Substances

13463-67-7 titanium dioxide 14808-60-7 Quartz (SiO2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous componen	ts:	
	Vinyl-Acrylic copolymer	10-25%
CAS: 57-55-6 EINECS: 200-338-0	Propylene Glycol substance with a Community workplace exposure limit	< 5%
CAS: 12174-11-7 EC number: 601-805-5	Attapulgite (Palygorskite) ★ Xn R40 Carc. 2, H351	< 5%
	(Contd	. on page 4

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

		(Contd. of page 3)
CAS: 9016-45-9	4-nonylphenyl-polyethylene glycol	< 1%
NLP: 500-024-6	Xi R36/38; 🜇 N R51/53	
	Aquatic Chronic 2, H411	
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 14808-60-7	Quartz (SiO2)	< 1%
EINECS: 238-878-4	□ T R49;	
	♦ Carc. 1A, H350	
	Petroleum Distillates	< 1,0%
	♦ Carc. 1B, H350	
· SVHC		
9016-45-9 4-nonylphe	enyl-polyethylene glycol	
· Dangerous Compone	ents (Alternative Classifications):	
CAS: 13463-67-7 t	itanium dioxide (classification relevant for USA/Canada only)	< 1%
EINECS: 236-675-5	🗞 Carc. 2, H351	
· Additional information	on: For the wording of the listed risk phrases refer to section 16.	
· Notable Trace Comp	onents (≤ 0,1% w/w)	
CAS: 1897-45-6	chlorothalonil (ISO)	
EINECS: 217-588-1 Index number: 608-01	W T+ R26; X Xn R40; Xi R37-41; Xi R43; N R50/5 4-00-4 Carc. Cat. 3 Xi R43; Xi	3
	♦ Acute Tox. 2, H330	
	& Carc. 2, H351	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	♦ Skin Sens. 1, H317; STOT SE 3, H335	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

(Contd. on page 5)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 4)

· 4.2 Most important symptoms and effects, both acute and delayed

Headache

Irritant to skin and mucous membranes.

Irritant to eyes.

Dizziness

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

· Hazards

May cause cancer.

May cause respiratory irritation.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

Water haze or fog

- · For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information No further relevant information available.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

(Contd. on page 6)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 5)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Avoid splashes or spray in enclosed areas.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Store away from oxidising agents.

- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients v	· Ingredients with limit values that require monitoring at the workplace:			
57-55-6 Propylene Glycol				
WEEL (USA)	Long-term value: 10 mg/m ³			
EV (Canada)	Long-term value: 155* 10** mg/m³, 50* ppm *vapour and aerosol;**aerosol only			
14808-60-7 Q	uartz (SiO2)			
PEL (USA)	see Quartz listing			
REL (USA)	Long-term value: 0,05* mg/m³ *respirable dust; See Pocket Guide App. A			
TLV (USA)	Long-term value: 0,025* mg/m³ *as respirable fraction			
EL (Canada)	Long-term value: 0,025 mg/m³ ACGIH A2; IARC 1			
EV (Canada)	Long-term value: 0,10* mg/m³ *respirable fraction (Contd. on page 7)			

(Contd. on page 7)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 6)

- · **DNELs** No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Suitable respiratory protective device recommended.

Use suitable respiratory protective device when aerosol or mist is formed.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

- · Body protection: Protective work clothing
- · Limitation and supervision of exposure into the environment

No further relevant information available.

· Risk management measures

See Section 7 for additional information.

No further relevant information available.

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 7)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Colour: Not determined.

· Odour: Mild

Odour threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Plash point:
Flammability (solid, gaseous):
Auto/Self-ignition temperature:
Not Determined.
212° F/ 100 °C
Not applicable.
Not applicable.

• **Self-igniting:** Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

Not determined.

· Explosion limits:

Lower: Not determined. **Upper:** Not determined.

Vapour pressure at 20 °C:
Density at 20 °C:
Relative density
Vapour density at 20 °C
Evaporation rate at 20 °C
23 hPa
1,32 g/cm³
Not determined.
> 1 g/cm³ (AIR = 1)
~ 1 (Water = 1)

· Solubility in / Miscibility with

· Decomposition temperature:

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

VOC content: 1.7 %

• 9.2 Other information No further relevant information available.

(Contd. on page 9)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 8)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· 10.3 Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong acids and oxidising agents.

· 10.4 Conditions to avoid

Keep away from heat and direct sunlight.

Store away from oxidising agents.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Hydrogen chloride (HCI)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

May cause cancer.

- · Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.
- · Repeated dose toxicity: May cause damage to organs through prolonged or repeated exposure.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):

Carc. 1A

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: The product contains materials that are harmful to the environment.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish

(Contd. on page 10)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 9)

- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Harmful to aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· DOT, ADR, ADN, IMDG, IATA Not Regulated

· 14.2 UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Not Regulated

· 14.3 Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Not Regulated

· 14.4 Packing group

· DOT, ADR, IMDG, IATA Not Regulated

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

(Contd. on page 11)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

(Contd. of page 10)

SECTION 15: Regulatory information	
 15.1 Safety, health and environmental regulations/legislation specific for the subs United States (USA) SARA 	stance or mixture
· Section 355 (extremely hazardous substances):	
None of the ingredients are listed.	-
· Section 313 (Specific toxic chemical listings):	
None of the ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65 (California):	
Chemicals known to cause cancer:	
12174-11-7 Attapulgite (Palygorskite)	
13463-67-7 titanium dioxide	
14808-60-7 Quartz (SiO2)	
1309-64-4 antimony trioxide	
1897-45-6 chlorothalonil (ISO)	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients are listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients are listed.	
· Carcinogenic Categories	
· EPA (Environmental Protection Agency)	
None of the ingredients are listed.	
· IARC (International Agency for Research on Cancer)	
12174-11-7 Attapulgite (Palygorskite)	2B
9002-86-2 polyvinyl chloride	3
13463-67-7 titanium dioxide	2B
14808-60-7 Quartz (SiO2)	1
· TLV (Threshold Limit Value established by ACGIH)	
9002-86-2 polyvinyl chloride	A4
13463-67-7 titanium dioxide	A4
14808-60-7 Quartz (SiO2)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 titanium dioxide	
14808-60-7 Quartz (SiO2)	
	(Contd. on page 12

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

· Canada

(Contd. of page 11)

- · Canadian Domestic Substances List (DSL)
 - All ingredients are listed.
- · Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients are listed.

· Canadian Ingredient Disclosure list (limit 1%)

57-55-6 Propylene Glycol

· Other regulations, limitations and prohibitive regulations

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· Substances of very high concern (SVHC) according to REACH, Article 57

9016-45-9 4-nonylphenyl-polyethylene glycol

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H350 May cause cancer.
- H351 Suspected of causing cancer.
- H411 Toxic to aquatic life with long lasting effects.

R36/38 Irritating to eyes and skin.

- R40 Limited evidence of a carcinogenic effect.
- R48 Danger of serious damage to health by prolonged exposure.
- R49 May cause cancer by inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 13)

Printing date 07.11.2014 Revision: 07.10.2014

Trade name: Eco-Perm Coating

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Carc. 1A: Carcinogenicity, Hazard Category 1A
Carc. 1B: Carcinogenicity, Hazard Category 1B
Carc. 2: Carcinogenicity, Hazard Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

(Contd. of page 12)