

Nashua 324A UL 181A-P & B-FX Listed Premium Cold Weather Foil Tape - 324A

Product Information Sheet

SKU/Product ID/Reference

324A

Product Description

UL 181A-P & B-FX Listed Premium Cold Weather Foil Tape for HVAC



Features and Benefits

- Aggressive Cold Weather Acrylic Adhesive
 - Superior performance ion all climate conditions
 - Resists mold and mildew growth
- UL 181A-P & B-FX Listed
 - Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Low VOC Content
 - Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Regions Available

Global

Product Information

Adhesive Type	Acrylic
Carrier / Support / Facestock	Foil
Carrier Thickness (mil)	2.1 mils
Gauge / Mil	4.8 mil
Liner Type	Paper
OEM / Specification Body & Specification	UL > 181A-P Listed UL > 181B-FX Listed
Operating Temp Range	-25 to 325 °F
Performance Category / Characteristics	Environmental Resistance Low VOC
Color(s)	Custom Color
Custom color(s)	Aluminum - Printed
Product Construction	Single-Coated Tape

berryglobal.com

Specifications are subject to change without notice.

This website uses cookies to enhance user experience and to analyze performance and traffic on our website. We also share information about your use of our site with our social media, advertising and

[Do Not Sell My Personal](#)