



Builder's Best, Inc.
 201 Broiles Drive
 Jacksonville, TX 75766
 888-368-7233
 fax: 800-259-8368
 www.BuildersBest.com

3" STANDARD VINYL HOSE



PRODUCT SPECIFICATIONS

- Vinyl Tubing
- High tensile steel wire, wound helix
- Permanently heat-sealed, between layers of PVC
- Polyvinyl Chloride Film
- Self Extinguishing
- Bend radius one diameter
- Useful as bathroom fan venting
- Not approved for dryer venting
- 1" Pitch

PART NUMBERS

Diameter	Length	Part#	Qty	Package
3"	5'	110562	12	bulk
	8'	110563	12	bulk
	8'	010558	90	bulk
	20'	110753	28	bulk
	20'	110564	5	ind box
3 1/4"	50'	110565	4	ind box
	20'	110054	28	bulk
	50'	110055	4	ind box

PERFORMANCE DATA

- Recommended Operating Pressure
 Positive: 4" WC max
 Negative: 1" WC max
- Maximum Velocity 3.1 5000 FPM
- Temperature Range -10°F to +120°F

LABELS



Made in the U.S.A.

WARRANTY

Manufacturer assumes no responsibility for failure due to improper installation. All specifications and designs are subject to change without notice and without incurring liability.

WARRANTY EXCLUSION AND DISCLAIMER Seller specifically excludes, and hereby disclaims any express representation or express warranty of any kind with respect to the goods ordered hereunder. All implied warranties, including without limitation merchantability or fitness for a particular purpose or arising from a course of dealing or usage or trade shall expire and cease 45 days after date of delivery. Seller shall not be liable to buyer or any third party for any special, secondary, incidental, or consequential damages however arising. Nothing in this provision shall invalidate or restrict any right or remedy otherwise available under state or federal law. Materials and specifications subject to change without notice.

3" Standard Vinyl Hose V1 11/19/14