Safety Data Sheet

Printing date 02.05.2014

Revision: 02.05.2014

1 Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

[.] Trade name: Nu-Foam 4293-04, 4293-75

• Article number: EHS 9885

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Sealant

1.3 Details of the supplier of the Safety Data Sheet
Supplier: Nu Calgon
2008 Altom Court
St. Louis, MO 63146
Phone: 800-554-5499

• **1.4 Emergency telephone number:** ChemTel Inc. (800)255-3924, +1 (813)248-0585

2 Hazards identification

· 2.1 Classification of the substance or mixture

The following Hazard Statements are applicable only to the general GHS regulations and not the specific CLP regulation: H222.



H222: Extremely flammable aerosol.



×		
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.



H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
	H315 H319

(Contd. on page 2)

٦

Safety Data Sheet

Printing date 02.05.2014

STOT SE	3 H335	May cause respi	ratory irritation.	(Contd. of pa
Classifica	ition according	to Directive 67/548	EEC or Directive	e 1999/45/EC
The produ preparatio Warning! Classifica The class literature of The class	ict has to be labe ins of the EU" in Pressurized con- ation system: sification is acco lata. sification is in a	the latest valid version tainer. ording to the latest accordance with the	ulation procedure of on. editions of the E	nvironment: of the "General Classification guideline EU-lists, and extended by company of international substances lists, an ormation provided by the company.
2.2 Label	-		erature and by inic	Simation provided by the company.
CLP regul	ring Hazard Stat ation: H222. remely flammab Harmful if inha Causes skin ir	le aerosol. aled.	le only to the gen	neral GHS regulations and not the spe (Contd. on pa

Safety Data Sheet

Printing date 02.05.2014

Trade name: Nu-Foam

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H335 May cause an allergic skin reaction. H373 May cause damage to organs through prolonged or repeated exposure. • Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P211 Do not spray on an open flame or other ignition source. P280 Wear protective gloves / eye protection. P340 Keep away from heat/sparks/open flames/hot surfaces No smoking. P214 Do not spray on an open flame or other ignition source. P280 Do not breathe mist/vapours/spray. P344 Get medical advice/attention if you feel unwell. P342+P311 resperiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. • Hazard description: • Haitmask WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol		
H334May cause allergy or asthma symptoms or breathing difficulties if inhaled.H337May cause an allergy is extended to organs through prolonged or repeated exposure.H337May cause damage to organs through prolonged or repeated exposure.Precautionary statementsP210Keep away from heat/sparks/open flames/hot surfaces No smoking.P251Pressurized container: Do not pierce or burn, even after use.P280Wear protective gloves / eye protection.P280Do not breathe mist/vapours/spray.P314Get medical advice/attention if you feel unwell.P342+P311ft experimentory symptoms: Call a POISON CENTER/doctor.P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.Additional information:Contains isocyanates. May produce an allergic reaction.Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.Buildup of explosive mixtures possible without sufficient ventilation.Hazard description:VHMINS-symbols:A - Compressed gasB5 - Flammable aerosolD2A - Very toxic material causing other toxic effectsImage: Pier = 4 Reactivity = 1Halth = 2 Fier = 4 Reactivity = 1* - Indicates a long term health hazard from repeated or prolonged exposures.HMIS Long Term Health hazard from repeated or prolonged exposures.HMIS Long Term Health hazard Substances9016-87-9Ghip		(Contd. of page 2)
H335 May cause damage to organs through prolonged or repeated exposure. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P280 Wear protective gloves / eye protection. P280 Do not spray on an open flame or other ignition source. P280 Do not breathe mist/vapours/spray. P314 Get medical advice/attention if you feel unwell. P342+P311 fexperiatory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMINS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Image: Pier = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4)		
H373 May cause damage to organs through prolonged or repeated exposure. Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P280 Wear protective gloves / eye protection. P280 Do not breathe mist/vapours/spray. P311 Get medical advice/attention if you feel unwell. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Very toxic material causing other toxic effects Very toxic scale 0 - 4). Fire = 4 Reactivity = 1 <td></td> <td></td>		
Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P211 Do not spray on an open flame or other ignition source. P280 Wear protective gloves / eye protection. P260 Do not breathe mist/vapours/spray. P314 Get medical advice/attention if you feel unwell. P342+P311 fexperiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Image: Pire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4). Image: Pire = 4 Rea		
P210 Keep away from heat/sparks/open flames/hot surfaces No smoking. P251 Pressurized container: Do not pierce or burn, even after use. P280 Wear protective gloves / eye protection. P280 Do not breathe mist/vapour/sypray. P314 Get medical advice/attention if you feel unwell. P342+P3111 fexperiencing respiratory symptoms. Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Very Pire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) Part = 2 Pire = 4 Reactivity = 1 - Indicates a long term health hazard from repeated or		d or repeated exposure.
P251 Pressurized container: Do not pierce or burn, even after use. P211 Do not spray on an open flame or other ignition source. P280 Wear protective gloves / eye protection. P280 Do not breathe mist/vapours/spray. P314 Fermedical advice/attention if you feel unwell. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Image: protective pr		urfaces No smoking
P211Do not spray on an open flame or other ignition source.P280Wear protective gloves / eye protection.P280Do not breathe misiVapours/spray.P314Get medical advice/attention if you feel unwell.P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.Additional information:Contains isocyanates. May produce an allergic reaction.Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.Buildup of explosive mixtures possible without sufficient ventilation.Hazard description:WHMIS-symbols:A - Compressed gasB5 - Flammable aerosolD2A - Very toxic material causing other toxic effects $\overbrace{volume}{volume}$ $\overbrace{volume}{volume}$ $volume$ Weathins:NEPA ratings (scale 0 - 4) $\overbrace{volume}{volume}$ <th< td=""><td></td><td></td></th<>		
 P280 Wear protective gloves / eye protection. P260 Do not breathe mist/vapours/spray. P314 Get medical advice/attention if you feel unwell. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight ad do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Will Second a second by a seco		
 P260 Do not breathe mist/vapours/spray. P314 Get medical advice/attention if you feel unwell. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Filammable aerosol D2A - Very toxic material causing other toxic effects With a served be account of the served be account of		
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects WFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues		
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects \overrightarrow{VO} \overrightarrow{VO} \overrightarrow{VO} Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) \overrightarrow{VERE} Health = *2 \overrightarrow{VEE} \overrightarrow{VEE} \overrightarrow{VEE} Health = *2 \overrightarrow{VEE} \overrightarrow{VEE}		
Additional information: Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Image: Scale 0 - 4) Image: Scale 0 -		
Contains isocyanates. May produce an allergic reaction. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects NFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH [2] Health = *2 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	• • •	atures exceeding 50 °C/122 °F.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects WFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) Health = *2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) Health = *2 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues		
 pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHIMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Wire a strain of the stra		and to tompore turns available 50°C. Do not
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Image: Source of the second state of the se		bose to temperatures exceeding 50°C. Do not
 smoking. Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects Without a strain of the strain of the		rial Keen away from sources of ignition - No
Buildup of explosive mixtures possible without sufficient ventilation. Hazard description: WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects		hai. Neep away nom sources of ignition - No
Hazard description:WHMIS-symbols:A - Compressed gasB5 - Flammable aerosolD2A - Very toxic material causing other toxic effects \widehat{OO} </td <td>0</td> <td>tilation</td>	0	tilation
 WHMIS-symbols: A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects WFPA ratings (scale 0 - 4) NFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH P Health = *2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH P Health = *2 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 		
A - Compressed gas B5 - Flammable aerosol D2A - Very toxic material causing other toxic effects NFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) Health = *2 Fire = 4 Reactivity = 1 Health = *2 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues		
D2A - Very toxic material causing other toxic effects NFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH [2] Health = *2 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues		
 NFPA ratings (scale 0 - 4) Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 2 Fire = 4 Reactivity = 1 Health = *2 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 		
Health = 2 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH [2] Health = *2 FIRE 4 Fire = 4 REACTIVITY 1 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	D2A - Very toxic material causing other toxic effects	
Health = 2 Fire = 4 Reactivity = 1 • HMIS-ratings (scale 0 - 4) HEALTH ¹² FIRE 4 Fire = 4 Fire = 4 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	NFPA ratings (scale 0 - 4)	
 Fire = 4 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH [2] FIRE 4 FIRE 4 REACTIVITY 1 Reactivity = 1 Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues 		
 Reactivity = 1 HMIS-ratings (scale 0 - 4) HEALTH 2 Health = *2 FIRE 4 Fire = 4 REACTIVITY 1 Reactivity = 1 Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues 		
HEALTH *2 HEALTH *2 FIRE 4 FIRE 4 Fire = 4 REACTIVITY Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues		
HEALTH 12 HEALTH 12 FIRE 4 Fire = 4 REACTIVITY Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues		
FIRE 4 FIRE 4 REACTIVITY 1 Reactivity = 1 1 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	[·] HMIS-ratings (scale 0 - 4)	
FIRE 4 FIRE 4 REACTIVITY 1 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	\mathbf{H}	
REACTIVITY 1 Reactivity = 1 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues		
 * - Indicates a long term health hazard from repeated or prolonged exposures. • HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues 	$\frac{10}{10} = \frac{4}{10}$ $\frac{10}{10} = \frac{1}{10}$	
• HMIS Long Term Health Hazard Substances 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	-	
9016-87-9 diphenylmethanediisocyanate,isomeres and homologues		longed exposures.
	5	
101-68-8 4,4'-methylenediphenyl diisocyanate		nologues
2.3 Other hazards		
Results of PBT and vPvB assessment		
• PBT: Not applicable.	· PBI: Not applicable.	(Contd on serve 1)
(Contd. on page 4)		(Conto, on page 4)

(Contd. of page 3)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 02.05.2014

Revision: 02.05.2014

Trade name: Nu-Foam

· **vPvB:** Not applicable.

•	tances listed below with nonhazardous additions.	
 Dangerous components: 		
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	20-40%
	 Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 	
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9	4,4'-methylenediphenyl diisocyanate	10-20%
	 Resp. Sens. 1, H334; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 	
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate R52/53	10-20%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether	5-10%
Index number: 603-019-00-8	Flam. Gas 1, H220 Press. Gas, H280	-
CAS: 72-28-5	Isobutane	1-5%
	🚸 Flam. Gas 1, H220	
CAS: 74-98-6 EINECS: 200-827-9	propane	1-5%
Index number: 601-003-00-5	Flam. Gas 1, H220 Press. Gas, H280	

4 First aid measures

· 4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

(Contd. on page 5)

GHS

Revision: 02.05.2014

Printing date 02.05.2014

Trade name: Nu-Foam	
	(Contd. of page 4)
Provide oxygen treatment if affected person has difficulty breathing.	(10)
In case of unconsciousness place patient stably in side position for transportation.	
· After skin contact:	
Immediately wash with water and soap and rinse thoroughly.	
Do not pull solidified product off the skin.	
If skin irritation continues, consult a doctor.	
· After eye contact:	
Immediately remove contact lenses if possible.	
Rinse opened eye for several minutes under running water. Then consult a doctor.	
· After swallowing:	
Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately.	
· 4.2 Most important symptoms and effects, both acute and delayed	
Asthma attacks	
Headache	
Breathing difficulty	
Allergic reactions	
Coughing	
Nausea	
Gastric or intestinal disorders when ingested.	
Irritant to skin and mucous membranes.	
Irritant to eyes.	
Dizziness	
Disorientation	
·Hazards	
Danger of impaired breathing.	
Danger of disturbed cardiac rhythm.	
Danger of pulmonary oedema.	
Danger of pneumonia.	
Danger of convulsion.	
• 4.3 Indication of any immediate medical attention and special treatment needed	
Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible. Treat skin and mucous membrane with antihistamine and corticoid preparations.	
In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.	
Monitor circulation.	
If necessary oxygen respiration treatment. Medical supervision for at least 48 hours. Contains isocyanates. May produce an allergic reaction. 5 Firefighting measures	

5 Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Water in flooding quantities.

- For safety reasons unsuitable extinguishing agents: None.
- \cdot 5.2 Special hazards arising from the substance or mixture

Danger of receptacles bursting because of high vapour pressure when heated.

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

GHS

Printing date 02.05.2014

Revision: 02.05.2014

Trade name: Nu-Foam

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

6 Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Keep away from ignition sources. Protect from heat. Isolate area and prevent access. Keep people at a distance and stay on the windward side. • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Allow to solidify. Pick up mechanically. Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to item 13. · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Emergency cooling must be available in case of nearby fire.

(Contd. on page 7)

GHS

Printing date 02.05.2014

Revision: 02.05.2014

Trade name: Nu	Trade name: Nu-Foam				
		(Contd. of page 6)			
· 7.2 Conditio	ns for safe storage, including any incompatibilities				
· Storage:					
 Requiremen Store in a con 	ts to be met by storerooms and receptacles: ol location.				
Provide venti	ial regulations on storing packagings with pressurized containers. lation for receptacles.				
	e near extreme heat, ignition sources or open flame.				
	about storage in one common storage facility:				
	om foodstuffs.				
	om oxidizing agents.				
	rmation about storage conditions: heat and direct sunlight.				
	ol place. Heat will increase pressure and may lead to the receptacle bursting.				
	end use(s) No further relevant information available.				
8 Exposure	controls/personal protection				
· Additional ir	formation about design of technical facilities: No further data; see item 7.				
ا 8.1 Control [.]	parameters				
· Ingredients	with limit values that require monitoring at the workplace:				
101-68-8 4,4	-methylenediphenyl diisocyanate				
PEL (USA)	Ceiling limit: 0,2 mg/m³, 0,02 ppm				
REL (USA)	Long-term value: 0,05 mg/m³, 0,005 ppm				
	Ceiling limit: 0,2* mg/m³, 0,02* ppm				

	*10-min	
TLV (USA)	Long-term value: 0,051 mg/m ³ , 0,005 ppm	
EL (Canada)	Short-term value: C 0,01 ppm Long-term value: 0,005 ppm Skin; S	
EV (Canada)	Long-term value: 0,005 ppm	
115-10-6 dim	ethyl ether	
IOELV (EU)	Long-term value: 1920 mg/m ³ , 1000 ppm	
WEEL (USA)	Long-term value: 1000 ppm	
EL (Canada)	Long-term value: 1000 ppm	
72-28-5 Isobutane		
REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm	
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm	

 EL (Canada)
 Short-term value: 750 ppm

 EV (Canada)
 Short-term value: 600 ppm

 EV (Canada)
 Long-term value: 800 ppm

 74-98-6 propane
 PEL (USA)

 PEL (USA)
 Long-term value: 1800 mg/m³, 1000 ppm

(Contd. on page 8)

GHS

Printing date 02.05.2014

Trade name: Nu-Foam

(Contd. of page 7) REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F: minimal oxygen content EL (Canada) Long-term value: 1000 ppm EV (Canada) Long-term value: 1,000 ppm · DNELs No further relevant information available. · PNECs No further relevant information available. · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eves and skin. Clean skin thoroughly immediately after handling the product. **Respiratory protection:** Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities. Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

No further relevant information available.

(Contd. on page 9)

(Contd. of page 8)

Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 02.05.2014

_ _ _

Revision: 02.05.2014

Trade name: Nu-Foam

[.] Risk management measures

See Section 7 for additional information. No further relevant information available.

9 Physical and chemical properties		
 9.1 Information on basic physical and General Information Appearance: 	chemical properties	
Form: Colour: · Odour:	Aerosol Amber coloured Light Petroleum-like	
· Odour threshold:	Not determined.	
pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not Determined. -44 °F / -42 °C (propellant)	
[·] Flash point:	-155 °F / -104 °C (propellant)	
[.] Flammability (solid, gaseous):	Not applicable.	
· Auto/Self-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not self-igniting.	
[.] Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
[·] Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapour pressure:	Not determined.	
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1,01 g/cm ³ Not determined. Not determined. Not applicable.	
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water)	Not determined.	
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.	
	(Contd. on page 10	

Revision: 02.05.2014

Printing date 02.05.2014

rade name: Nu-Foam	
	(Contd. of page
· Solvent content:	
VOC (US EPA Method 24)	155 g/l
• 9.2 Other information	No further relevant information available.
0 Stability and reactivity	
· 10.1 Reactivity	
 10.2 Chemical stability 	
Thermal decomposition / conditi	
No decomposition if used and store	
10.3 Possibility of hazardous rea	
Develops readily flammable gases/	fumes.
Flammable.	
Reacts with oxidizing agents.	if heated above flash point and/or when sprayed or atomised.
	ause of high vapour pressure when heated.
Contact with acids releases toxic ga	
	ated above the decomposition point.
10.4 Conditions to avoid	F F
Keep ignition sources away - Do no	ot smoke.
Store away from oxidizing agents.	
	urther relevant information available.
 10.6 Hazardous decomposition p 	
Carbon monoxide and carbon dioxi	de
Nitrogen oxides (NOx)	
Hydrogen cyanide (prussic acid) Phosphorus oxides (e.g. P2O5)	

 11.1 Information on toxicological effects Acute toxicity: 		
· LD/LC50 values relevant for classification:		
101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral LD50 2200 mg/kg (mouse)		
 Primary irritant effect: on the skin: Irritant to skin and mucous membranes on the eye: Irritating effect. Sensitization: Sensitization possible through inhalation. Sensitization possible through skin contact. Subacute to chronic toxicity: Inhalation of concentrated vapours as well as ora headache, dizziness, etc. 		

GHS

Printing date 02.05.2014

Trade name: Nu-Foam

Revision: 02.05.2014

· Additional toxicological information:

(Contd. of page 10)

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful Irritant

Danger through skin adsorption.

Toxic and/or corrosive effects may be delayed up to 24 hours.

In addition to local irritant manifestations, there is a narcotic effect when inhaling high concentrations, with high danger of central respiratory arrest.

Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.

Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

12 Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes:

Avoid transfer into the environment.

Harmful to aquatic organisms

This statement was deduced from products with a similar structure or composition.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· 14.1 UN-Number

· DOT, ADR, IMDG, IATA

UN1950

(Contd. on page 12)

Printing date 02.05.2014

Trade name: Nu-Foam				
(Contd. of page 11)				
kg (66 lb) and inner packagings less than 1 L (0.3				
rosols, flammable 50 AEROSOLS, flammable ROSOLS, flammable				
5F Gases.				
t Regulated arning: Gases. D,S-U ot applicable.				
(Contd. on page 13)				

Printing date 02.05.2014

Revision: 02.05.2014

Trade name: Nu-Foam

Г

· UN "Model Regulation":

UN1950, AEROSOLS, flammable, 2.1

(Contd. of page 12)

 15.1 Safety, health and environmental regulations/legislation specific for t United States (USA) SARA 	the substance or mixtu
[·] Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	
101-68-8 4,4'-methylenediphenyl diisocyanate	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65 (California):	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic Categories	
EPA (Environmental Protection Agency)	
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	CBD
101-68-8 4,4'-methylenediphenyl diisocyanate	D, CE
IARC (International Agency for Research on Cancer)	i
9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	
101-68-8 4,4'-methylenediphenyl diisocyanate	
TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
Canada	-
Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
Canadian Ingredient Disclosure list (limit 0.1%)	

Printing date 02.05.2014

Revision: 02.05.2014

(Contd. of page 13)

Trade name: Nu-Foam

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eve irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- R12 Extremely flammable.
- Harmful by inhalation. R20

R36/37/38 Irritating to eyes, respiratory system and skin.

- R42/43 May cause sensitisation by inhalation and skin contact.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- WHMIS: Workplace Hazardous Materials Information System (Canada)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas

(Contd. on page 15)

Printing date 02.05.2014

Revision: 02.05.2014

Trade name: Nu-Foam

(Contd. of page 14)

Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Stin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 **Sources** SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com