



- 2P** Commercial 2 Time Periods (Occupied/Unoccupied)
- 7D** 7 Day Programmable
- 5/1/1** 5/1/1 Programmable
- NP** Non-programmable

- Stages of Heat
- Stages of Cool
- Gas, Electric or Oil
- Heat Pump
- Millivolt
- Battery Power
- 24V Power (Hardwire)
- Dual Fuel Compatible
- Display Size (Square Inches)
- Auto Changeover
- Filter Change Reminder
- Room Temperature Calibration
- Minimum Compressor Run Time
- Compressor Short Cycle Delay
- Adjustable Heat & Cool Temperature Swing
- Cooling Fan Delay
- High and Low Speed Fan Switch
- Programmable Fan
- Keypad Lockout
- Adjustable Setpoint Limits
- Humidity Control
- Memory Type (Permanent)
- Touchscreen
- Warranty (Years)
- Remote Sensor Capable

Terminals



Pro1 Model #	Programmability			Features																Terminals											
	7D	5/1/1	NP	Stages of Heat	Stages of Cool	Gas, Electric or Oil	Heat Pump	Millivolt	Battery Power	24V Power (Hardwire)	Dual Fuel Compatible	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Minimum Compressor Run Time	Compressor Short Cycle Delay	Adjustable Heat & Cool Temperature Swing	Cooling Fan Delay		High and Low Speed Fan Switch	Programmable Fan	Keypad Lockout	Adjustable Setpoint Limits	Humidity Control	Memory Type (Permanent)	Touchscreen	Warranty (Years)	Remote Sensor Capable		
Wireless																															
Z955W«	7D	5/1/1	NP	3*	2	H	13	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O
T955WH**	7D	5/1/1	NP	3*	2	H	13	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, H, D	
T631W-2	NP			2	1		2	5	R, C, Y, W, GH, GL, O/B		
Wired																															
T955	7D	5/1/1	NP	2P	3*	2	S	13	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O		
T925	7D	5/1/1	NP		3	2	S	13	5	R, C, Y, Y2, W2, E, G, B, O, L		
T905	7D	5/1/1	NP		1	1		13	5	Rh, Rc, C, Y, W, G, B, O		
BETTER																															
T855	7D	5/1/1	NP	2P	3*	2	S	8	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O		
T805	7D	5/1/1	NP		1	1		8	5	Rh, Rc, C, Y, W, G, B, O		
T801	NP				1	1		8	5	Rh, Rc, C, Y, W, G, B, O		
GOOD																															
T771	NP			0/1	0/1		4	5	R, C, W/Y, G		
T755H	5/1/1	NP		3*	2	S	6	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, H, D		
T755S ^{ΔΔ}	5/1/1	NP		3*	2	H	6	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, S1, S2		
T755	5/1/1	NP		3*	2	S	6	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O		
T725	5/1/1			2	1	S	4	5	R, C, Y, W2, E, G, B, O		
T721	NP			2	1	S	4	5	R, C, Y, W2, E, G, B, O		
T715	5/1/1			2	2		4	5	R, C, Y, Y2, W, W2, G		
T705	5/1/1			1	1		4	5	Rh, Rc, C, Y, W, G, B, O		
T701	NP			1	1		4	5	Rh, Rc, C, Y, W, G, B, O		
BUILDER																															
T621-2	NP			2	1	S	2	5	R, C, Y, W2, E, G, B, O		
T605-2	5/1/1			1	1		2	5	Rh, Rc, C, Y, W, G, B, O		
T601-2	NP			1	1		2	5	Rh, Rc, C, Y, W, G, B, O		
T601	NP			1	15	5	Rh, Rc, C, Y, W, G, B, O		

PRO1 NUMBERING	Prefix		First Number		Second Number		Third Number		Suffix						
	T	thermostats	DA	discharge air sensor	6	600 platform	8	800 platform	0	single stage	1	non programmable	W	Wireless	S
R	remote sensor			7	700 platform	9	900 platform	3	universal single stage	5	programmable	H	Humidity control		
Z	zoning capable							5	multi stage gas	7	heating or cooling	-2	Series Number		
								2	multi stage heat pump						

« Wireless Zoning thermostat for up to five zones. Accessories available for Z955W are RZ251W (Secondary Zone Sensor), Z260W (Damper Module), ZDA250W (Discharge Air Sensor), Z250W (Outdoor Air Sensor).

** Wireless accessories available for T955WH. R251W is an Indoor Remote Temperature Sensor. R250W is an Outdoor Remote Temperature Sensor. W150W is a Wireless repeater to extend wireless range for wireless thermostats and remotes.

ΔΔ Wired accessories available for T755S. R251S is an Indoor Remote Temperature Sensor. R250S is an Outdoor Remote Temperature Sensor / Slab Sensor.

* 3 heat stages for heat pump or 2 heat stages for conventional. H Dual Fuel Hardware Balance Point. Requires Outdoor Temperature Accessories R250W or R250S. S Dual fuel software setting. Y de-energizes when W2 energizes.



T900 Family



T800 Family



T700 Family



T600 Family



WIRELESS WIRE®



Wireless Wire® was developed jointly with HVAC professionals. Wireless Wire® functionally replaces 24 VAC control wiring. Simply connect the terminals on one module and when those terminals see 24V then the same terminals on the other module close. Wireless Wire® is another Pro1 innovation offered exclusively to our professional HVAC contractor partners.

Pro1 wireless control system.



Pro1 IAQ Inc.
1111 S. Glenstone
Suite 2-100
Springfield, MO 65804
Toll-free: 1-888-Pro1iaq (776-1427)
Toll Number (Outside the USA): 330-821-3600
Web: <http://www.pro1iaq.com>
Hours of Operation: Monday - Friday 9 AM - 6 PM Eastern

PRO1®
IAQ



Heavy duty products for the professional HVACR contractor.



The Pro1 difference.

- **Value**
Our Pro1 thermostats are contractor grade, built on the proven performance and reliability you expect. It's a difference you can feel.
- **One Size Thermostats**
All Pro1 thermostats share the same size footprint, so you never have to worry about wall marks left by old models. You can also upgrade to new models without replacing the subbase, just snap on the new model.
- **Display Size**
We boast the largest displays for the money. Homeowners want large displays and now you can give them what they've been asking for.
- **Badge System**
All Pro1 thermostats share a removable badge that can easily be replaced with a custom badge that has your contact information.



Removable Badge System

Are you a PRO1?