



TECHNICAL DATA SHEET



BIG-8 REFLECTIVE DUCT INSULATION (OUTDOOR)

Product Description:

rFOIL™ BIG-8 Reflective Duct Insulation consist of two layers of thick polyethylene bubble pack reflective insulation connected by 2-inch wide spacers.

Install the separate set of 2" Spacer Strips (included with the BIG-8 product) around the perimeter of the duct at every 2ft interval followed by wrapping the BIG-8 over the spacers. This product has on it a code certification strip that identifies the brand name and pertinent testing information for duct applications. This inspector friendly tape means no hassles at the jobsite and peace of mind for installers.

The Big-8 Reflective Duct Insulation has been tested to an R-8 and is classified as Class 2/Class B in accordance with the ASTM E84-09 fire test standard. The product was mounted in accordance to ASTM-E2599-08.

ALUMINUM SURFACE BUBBLE BUBBLE BUBBLE ALUMINUM BUBBLE SURFACE SUPPLIED SEPARATE SPACERS SUPPLIED SEPARATE SPACERS

Stock Sizes Available (Rolls):

Size	48" X 50'	48" X 75'
Part No.	9280-48-050	9280-48-075

(ICC-ES Evaluation Report ESR-1236)

Features:

- R-Value 8
- Approved vapor barrier protection
- Inhibits condensation, mould and fungi growth
- Improves HVAC system efficiency

- No foam corner spacers needed
- Thermal performance unaffected by moisture
- Non-Toxic / Non-Carcinogenic

Applications:

- Duct Insulation without spacers (R-8)

Physical Properties	Test	Value
THERMAL RESISTANCE	ASTM C335	R-8 with BUBBLE SPACERS
TEMPERATURE RANGE	ASTM C411	-50°F to 180°F
FIRE RATING	ASTM E84-09	CLASS 2 / CLASS B
EMISSIVITY	ASTM C1371	0.03
REFLECTIVITY	ASTM E903	0.97
WATER VAPOR PERMEABILITY	ASTM E96	0.029 Perms
RESISTANCE TO FUNGI & BACTERIA	ASTM C1338-08	DOES NOT PROMOTE GROWTH
BLEEDING and DELAMINATION	ASTM C1224-03	NO BLEEDING or DELAMINATION
PLIABILITY	ASTM C1224-03	NO CRACKING
TEMPERATURE and HUMIDITY RESISTANCE	ASTM C1258	Evidence of Delamination - NONE
		Evidence of Corrosion - NONE
		Loss of Metallaization - MINIMAL



PATENTS

US Patent No.: 8,221,871 US Patent No.: 8,327,601 US Patent No.: 8,343,614

US Patent No.: 7,935,410 US Patent No.: 7,935,411 CDN Patent No.: 2,554,754 CDN Patent No.: 2,591,589



279 Humberline Drive Etobicoke, ON M9W 5T6 Call Toll Free: 1-800-837-8961 Local: 416-798-1340 Fax: 416-798-1342 Email: sales@rfoil.com

Visit our Website: www.rfoil.com

Published: June 30, 2013

