ULTRA SERIES ULTRA120V



PERFORMANCE

Water Removal	124 Pints / 15.5 Gallons
Efficiency	7.6 Pints/kWh
Energy Factor	3.6 L/kWh
Blower	445 CFM @ 0.0" WG 390 CFM @ 0.2" WG 360 CFM @ 0.4" WG
Operating Temperature	49°F Min., 95°F Max.
Sizing	Up to 3,000 Sq. Ft. / 30,000 Cu. Ft.

ELECTRICAL

Power	680 watts @ 80°F and 60% R	Н
Supply Voltage	115 volt – 1 phase – 60 Hz	
Current Draw	5.8 amps	
Power Cord	9', 115 VAC, Ground	Plug Type B (USA, MEX, CAN, JPN)
Circuit Requirement	15 Amns	(USA, MEX, CAN, JPN)

SPECIFICATIONS

Duct Connections	6" Round Inlet, 8" Round Inlet, 8" Round Outlet (x2)
Drain Connection	3/4" Threaded Female NPT
Refrigerant	R410A, 2 lbs. 5 oz.
Unit Dimensions	26.75"W x 43.5"H x 18.75"D
Unit Weight	120 lbs.



Shipping Dimensions	25.25"W x 46.5"H x 22"D
Shipping Weight	145 lbs.
Pallet Quantity	1 per pallet
UPC Number	859029004663
Shipping Options	LTL

Specifications are subject to change without notice. Performance is based on pints / gallons per day @80°F/60%RH. Sizing is based on 10 foot ceiling height. Unit dimensions and weight are with collars on.



- 26 3/4" ---->

183/4"

-- 20 1/2"-->

Top



THE INDUSTRY'S ONLY
VERTICAL DEHUMIDIFIER
- FEATURES A SMALL
FOOTPRINT AND OPTIONAL
DUAL EXHAUST.

MODEL 4036400

FEATURES

- Vertical orientation for basements and mechanical rooms where floor space is limited
- + Engineered for low temperature operation providing comfort year round
- + Use of DEH 3000/R digital control for outdoor air ventilation and humidity control
- + Superior MERV-13 filtration to improve indoor air quality
- + Ducting option for fresh outdoor air ventilation
- + Push button reset for transformer protection









BUILT TO LAST. BUILT TO PERFORM.

ORDERING INFORMATION

FILTRATION



MERV-13 FILTER

- + Designed to trap particles down to 0.3 microns
- +90% ASHRAE Dust Spot
- + 16" x 20" x 2"



MERV-14 FILTER

- + Designed for high efficiency
- + Deep pleated 95% media filter
- + 16" x 20" x 4"

PART NO.	ITEM
4039391	MERV-13 Filter
4037733	MERV-13 Filter, 4-Pack
4037734	MERV-13 Filter, 12-Pack
4022489	MERV-14 Filter

INSTALLATION



DEH 3000 DIGITAL CONTROL

- + Precise monitoring and control of moisture levels
- + Manages fresh air filtration with optional damper
- + Activates air filtration





CONDENSATE PUMP

- + For use in spaces where gravity drain is not possible
- Includes 20-foot drain hose, giving the option to run longer distances (pump located inside the dehumidifier)
- + Pump features a float switch that directs it to run only when needed

PART NO. ITEM	PART	NO.	ITEM
---------------	------	-----	------

4039225 Condensate Pump

PARTS

4035852	Compressor
4034474-05	Evaporator Coil
4028566	Condenser Coil
4029510	Filter / Drier
4036164-03	Capillary Tubes
4038071	Fan (Blower)
4022484	Relay, SPST
4029575	Relay, DPDT
4033032-05	Run Capacitor
4035235-07	Fan Capacitor
4022487	Transformer
4036559	Circuit Breaker
4036523	Power Cord

4038968	Wire Harness
4036967	Defrost Thermostat
4035872	Overload, Compressor
4038967	Wiring Diagram
4026221	Leveling Feet
4029894	Hose, Drain Pan
4037789	Slide Latch
4038693	Hinge
4029828	Duct, Inlet, 8" Plastic
4029829	Duct, Inlet, 6" Plastic With Damper
4029588	Duct, Outlet, 8" Plastic

The Santa Fe team is available Monday - Friday, 8 am - 5 pm CT.

We want to hear from you, so don't hesitate to reach out.

Need help with a warranty claim? Contact us at 800-533-7533.

Contact Customer Service at orders@thermastor.com.

SANTA-FE-PRODUCTS.COM