

This material safety data sheet (MSDS) was prepared solely for the reference of, and as a courtesy to, Shurtape's customers. The adhesive tape product to which this MSDS refers is a manufactured item that meets the definition of an "article" under the OSHA Hazard Communication Standard (hereinafter "the Standard"), which exempts articles from the requirements of the Standard, including the requirement to provide an MSDS.

Under normal conditions of use this product is not expected to release hazardous chemicals, nor pose a physical hazard or health risk, such that the Standard would require Shurtape to provide an MSDS. However, failure to use this product in accordance with Shurtape's recommendations or under normal conditions could result in potential physical hazards, health risks, or other hazards.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

	PC 609 Series Pressure Sensitive			
General Name:	Таре	HMIS® III		
		PC 609 Series Pressure Sens	sitive Tape	
				Icons:
Shurtape Technol	ogies, LLC	Health	1	
PO BOX 1530		Flammability	1	
Hickory, N.C. 286	03-1530	Physical Hazard	0	
(828) 322-2700		Personal Protection	В	
Prepared Date:	7/9/2014	Prepared By: EHS Gr	oup	

HMIS III® Icons are used with permission of the American Coatings Association (ACA)

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS Number	<u>% Weight</u>
Polyethylene	Proprietary	15-45 %
Cloth	Proprietary	5-15 %
Rubber	Proprietary	10-25 %
Hydrocarbon Resin	Proprietary	10-30 %
Filler	Proprietary	10-30 %

3. HAZARDS IDENTIFICATION

Emergency Overview

May cause skin or eye irritation by mechanical abrasion or by sensitivity to polymers.

Note: If this product is subject to combustion it will undergo hazardous decomposition that will yield the formation and release of hazardous substances including but not limited to carbon dioxide, carbon monoxide, polycyclic organic matter, and smoke. Exposure may cause irritation of the eyes, skin, and respiratory tract. Symptoms such as coughing, tearing, and irritation should be regarded as potentially hazardous and measures should be taken to avoid exposure.



4. FIRST AID MEASURES

Eyes

If wearing contact lenses, remove. Hold eyelids apart and immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get medical attention if irritation persists.

Skin

Wash with soap and water. Seek medical attention if irritation develops or persists.

Ingestion:

Do not give anything by mouth to an unconscious person. Seek medical attention.

Inhalation

Not applicable.

5. FIRE FIGHTING MEASURES

Flash Point (°F)	Not Determined	Auto Ignition Temp (°F)	Not Determined
LEL	Not Determined	UEL	Not Determined

Hazardous Products of Combustion

If this product is subject to combustion it will undergo hazardous decomposition that will yield the formation and release of hazardous substances including but not limited to carbon dioxide, carbon monoxide, polycyclic organic matter, and smoke.

Fire and Explosion Hazards

Minimal fire hazard as supplied. Polymers in adhesive and polymer backed cloth will support

Extinguishing Media

X Foam X Water Spray X CO ₂ X Dry Chemical		ſ	Х	Foam	Х	Water Spray	Х		Х	Dry Chemical
---	--	---	---	------	---	-------------	---	--	---	--------------

Fire Fighting Instruction

Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Not applicable.

7. HANDLING AND STORAGE

Handling

Material will be tacky/sticky. Recommend the use of light weight cloth or leather gloves for actual handling of material.

Shurtape Technologies, LLC PO Box 1530, Hickory, NC 28803-1530 • Phone: (888) 442-8273 • Fax: (800) 335-7851

www.shurtape.com



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye Protection

Safety glasses with side-shields recommended

Skin Protection

Normal lightweight work clothing will minimize skin contact. Use of lightweight cloth or leather gloves recommended.

Respiratory Protections

No adverse respiratory exposure anticipated under normal use

Engineering Controls

No special engineering controls are required

Exposure Guidelines

Not applicable

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point	N/A	Melting Point	>100 <i>°</i> C
Specific Vapor Density	N/A	Percent Volatiles	<1%
Specific Gravity	N/A	Evaporation Rate	N/A
Appearance	Various Colors	State	Solid at Ambient Temperature
Odor	No Strong odor	рН	N/A
Viscosity	N/A	Freezing Point	N/A
Molecular Weight	N/A	Solubility in H₂O	negligible

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Not anticipated under normal or recommended handling, use, or storage conditions.

Hazardous Decomposition

None anticipated under normal or recommended handling, storage, and use conditions. If this product is subject to combustion it will undergo hazardous decomposition that will yield the formation and release of hazardous substances including but not limited to carbon dioxide, carbon monoxide, polycyclic organic matter and particulate matter. This is not the intended use for this product.

Chemical Stability

Stable

Incompatibility

Incompatible with: strong acids and oxidizing agents

Box 1530, Hickory, NC 28803-1530 • Phone: (888) 442-8273 • Fax: (800) 335-76 www.shurtape.com



11. TOXICOLOGICAL INFORMATION

Exposure to chemicals and possible effects will not occur with normal use.

12. ECOLOGICAL INFORMATION

No Data

13. DISPOSAL CONSIDERATION

Waste Management Information

This material is considered to be non-hazardous under EPA's RCRA regulations. Dispose of per appropriate local regulations. Shurtape® products are manufactured on a core using 90% recycled content and are packaged in containers with an average of 33% (5% pre-consumer and 28% post-consumer) recycled content. Additionally, the containers used to package Shurtape® products are 100% recyclable.

14. DOT Information - 49 CFR 172.101

DOT description:

Material is not a hazardous material when shipped

Container / Mode:

Various size packages can be utilized for shipping this material

NOS Component:

None

RQ (Reportable Quantity) – 49 CFR 172.101

Product Quantity (lbs) - None

Other Transportation Information:

The DOT Transport Information may vary with the container and mode of shipment

MATERIAL SAFETY DATA SHEET



15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status TSCA (UNITED STATES) The intentional ingredients of the product are listed.

CERCLA RQ – 40 CFR 302.4 (a) None

CERCLA RQ – 40 CFR 302.4 (b) None

SARA 302 Components – 40 CFR 355 Appendix A None

Section 311 / 312 Hazard Class - 40 CFR 370.2

Immediate (X) Delayed () Fire (X) Reactive () Sudden Release of Pressure () Immediate for the molten liquid state only

OSHA Process Safety Management 29 CFR 1910

None listed

EPA Accidental Release Prevention 40 CFR 68

None listed

State and Local Regulations

California Proposition 65

Please see the Regulatory Compliance Letter for the most current information.

International Regulations

EU Packaging Directives

Please see the Regulatory Compliance Letter for the most current information.

DSL (Canada)

The intentional ingredients of this product are listed.

REACH

Please see the Regulatory Compliance Letter for the most current information.

Shurtape Technologies, LLC PO Box 1530, Hickory, NC 28803-1530 • Phone: (888) 442-8273 • Fax: (800) 335-7851 www.shurtape.com

ISO 9001 CERTIFIED QUALITY SYSTEM



16. OTHER INFORMATION

The following information addresses the allowable credits that may be claimed in accordance with Green Building Rating System for New Construction and Major Renovations, version 2.2 Indoor Environmental Quality: EQ Credit 4.1: Low-Emitting Materials (p. 69): Adhesives & Sealants: Substrate Specific Applications: Metal to Metal: VOC content < 30 g/l [in accordance with SCAQMD Rule #1168] Actual VOC content: < 10 g/l [based upon testing conducted in accordance with SCAQMD Rule #1168] Credit: 1 point

The following information addresses the allowable credits that may be claimed in accordance with LEED® for Homes Rating System Materials and Resources: MR Credit 2.2: Environmentally Preferable Products: Table 24 – Environmentally Preferable Products : Adhesives and Sealants (see Table 26) Table 26 – Standards for Low-Emissions Adhesives and Sealants (meet SQAQMD Rule #1168) Substrate Specific Applications: Metal to Metal: VOC content < 30 g/l [in accordance with SCAQMD Rule #1168]

Actual VOC content: < 10 g/l [based upon testing conducted in accordance with SCAQMD Rule #1168] Credit 1/2 point

As defined by 29 CFR 1910. 1200, this product is considered to be an article, defined in the regulation as a "manufactured item other than a fluid or particle: (I) which is formed to a specific shape or design during manufacture; (II) has an end use function(s) dependent in whole or in part upon its shape or design during end use; and (III) which does not release more than very small quantities, e.g., minimal or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees."

This information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable for their circumstances.