

#### FOR INDUSTRY PROFESSIONALS



# ELECTRICAL TAPE





Our tape is 7 mil thick and measures 3/4" wide and 66' long. It is made according to industry standards. It can be used to insulate splices up to 600 volts.



Tape is made from a flame retardant material that is lead-free and resistant to the sun, oil, acids, alkalis, and corrosive materials.



Electrical tape can be used indoors or outdoors and can withstand temperatures ranging from 32–176 degrees Fahrenheit.

	TRADEPRO	SIZE	MATERIAL	COLOR	PACK QTY	CARTON QTY	UOM
RICAL PE	TP-ELECTAPE	3/4" x 66' x .007"	Vinyl	Black	1 Roll	144 Rolls	Roll
ELECT	TP-ELECTAPE-6	3/4" x 66' x .007"	Vinyl	Black	6 Rolls	24 Pack	Pack

### **Trade Pro Vinyl Electrical Tape**

**DESCRIPTION:** 7 mil (0.18mm) economy grade, weather resistant, pressure sensitive vinyl tape for all kinds of mechanical and electrical applications. Flame retardant and can be used as primary insulation for splices up to 600 volts.

**CERTIFICATIONS:** UL 510, CSA



**RECOMMENDED** Used for general splicing purposes. Can be used as primary insulation for splices USES: up to 600 volts and provides a protective outer jacket over splices at higher voltages. Can be used for wrapping wire harnesses and insulating degaussing coils.

FEATURES: · 7 mil thickness

- · Flame retardant
- · Lead-free
- · Resistant to sun, water, oil, acids, alkalies, corrosive chemicals

### STANDARD SIZES: 3/4" x 66' | 19mm x 20.1m

PROPERTY	VALUE	UNIT	TEST METHOD					
Physical								
Thickness	0.007	inch	ASTM-D-100					
THICKIESS	0.178	mm	A3111-D-100					
Tensile Strength	16	lb/in	ASTM-D-100					
	28.16	n/cm	A3111-D-100					
Elongation	150	%	ASTM-D-100					
Adhesion to Steel	20	oz/in	ASTM-D-100					
Adhesion to Steel	2.2	n/cm	A3111-D-100					
Adhesion to Backing	17	oz/in	ASTM-D-100					
Addesion to Backing	1.8	n/cm						
Flammability	4 max	second	ASTM-D-100					
Temperature Rating								
Maximum	80	٥C	UL 510					
Waxinum	80	٥C	CSA 22.2					
Minimum	0	٥C	UL 510					
	0	٥C	CSA 22.2					

Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the products suitability for the intended use



## Why Sell TradePro Electrical Tape

Trade Pro Electrical Tape is UL listed and CSA certified. It is designed for safety and ease of use.

Trade Pro Electrical Tape is also available in bulk.

ELECTRICAL TAPE						
3/4" x 66' x .007"	3/4" x 66' x .007"	SIZE				
6 Rolls	1 Roll	РАСК QTY				
TP-ELECTAPE-6 CET-01BLK-SL	TP-ELECTAPE	TRADEPRO				
CET-01BLK-SL	CET-01BLK	CAMBRIDGE				
	6-3460	CAMBRIDGE DIVERSITECH MARS				
	86133	MARS				
	EWG7060	NSI				

Cambridge, Diversitech, Mars, and NSI are trademarks of their respective owners.

Reasonable effort has been made to assure the accuracy of cross-reference information. However, final evaluation for suitable replacement is left to the installer.