


8-32 STUD, TYP (4)

7 LEADS WHT, YELLOW, ORG, RED, BLK, VIOLET & BLUE

#8-32 STUD, TYP (4)



CAT NO. 9664

MODEL K33NVWKK-1404 HP 1/12-1/20


VOLT 115/230 HZ 60 & 50 AMP 1.2-0.95/0.6-0.5 & 1.5-1.3/0.75-0.65

R.P.M. 1550 & 1300 THERMALLY PROTECTED

INS CL B 50° C AMB MFG. NO. (XXX)JU PH 1

AIR OVER CONT

CAP RATING 5MFD/370VAC



WARNING - FOLLOW ALL SAFETY INFORMATION TO REDUCE POTENTIAL ELECTRICAL SHOCK DISCONNECT POWER BEFORE SERVICING. FOLLOW NATIONAL AND LOCAL CODES FOR GROUNDING AND INSULATE UNUSED LEAD WIRES INDIVIDUALLY.

NIDEC MOTOR CORPORATION www.usmotors.com

MADE IN CHINA

ROTATION: CCW SHAFT END REV

115V	230V
WHITE — LINE	WHITE — LINE
YELLOW — INS	YELLOW — INS
ORANGE — INS	RED — INS
RED — INS	BLACK — INS
BLACK — LINE	ORANGE — INS
VIOLET — LINE	BLUE — LINE
BLUE — LINE	VIOLET — LINE
BROWN — INS	BROWN — INS
BROWN — INS	BROWN — INS

TO REVERSE ROTATION INTERCHANGE RED & BLUE LEADS

ALL DIMENSIONS ARE IN INCHES

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN	
K33NVWKK-1404	--	WHOLESALE-HAC	1/12-1/20	115/230	1.2-0.95/0.60.5 & 1.5-1.3/0.75-0.65	60 & 50	1550 & 1300	CCW SHAFT END REV	9664	
SHEET NUMBER 1 OF 1	REV F	REVISION RECORD FOR: C6377-00			INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION				NIDEC MOTOR CORPORATION	
REVISION DATE	REVISED AMB VALUE TO 50°C.									
31-AUG-12										
ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN										
ISSUED BY D. LIU			REVIEWED BY R. LI		ENGINEER APPROVED R. LI		TITLE ASSEMBLED VIEW			
							CODE V01	ITEM NO. 778391	SIZE B	