

Venture Tape® 1599B UL181B-FX Listed Flexible Duct Closure Tape







- <u>HALF THE COST</u> of cloth duct tape
- UL181B-FX Listed
- Higher adhesion and tack than traditional cloth duct tapes
- Can be used on metal & metal connections
- Excellent UV resistance
- Long-life CW acrylic adhesive; superior performance in extreme environments; from -40°F to 185°F
- 2 inch x 120 yard rolls





Venture Tayle Corp. 30 Commerce Rd., Rockland, MA 02370 Tel 781 33 200; Fax 781 871-0065

Technical Data Sheet

1599B UL-181B-FX Printed 3 Mil Flexible Duct Closure Tape

Description

A polypropylene film with an acrylic CW cold weather adhesive system. This adhesive performs well in either sub-zero cold or abnormally warm temperatures, including hot attics. Listed with Underwriters Laboratories and meets all requirements of UL 181B-FX for closure systems for use with flexible air ducts and air connectors.

This product can also be used on metal and metal connections.

Applications:

Primarily used for sealing flexible air ducts and air connectors.

Technical Data	Imperial	Metric	Test Method
Thickness	3.0 mils	0.08 mm	
Peel Adhesion	30 oz/in width	8.3 N/2.5 cm	PSTC 101
Shear (>24 hours)	2.2 psi	15.2 kPa	PSTC 107
Tensile	20 lb/inch	90.4 N/2.5 cm	PSTC 131
Elongation	130%	130%	PSTC 131
Temperature Range	-40° F to 185°F	-40° C to 85°C	
Mold Growth	0	0	
Roll Size	2" x 120 Yards	5.1 cm x 110 m	

Important Information:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Users must determine the product suitability for the end use application and assume all risks and liabilities.



GTA - NHT, Inc. Venture Tape 30 Commerce Rd., Rockland, MA 02370 Tel 781-331-5900; Fax 781-871-0065 800-343-1076 (U.S.A.), 800-544-1024 (Canada) Toll Free Fax 877-264-5490 www.venturetape.com

