VIVE™

COMFORT

Mon
10:03 AM
Set At 74
Temperature
74 °F

Menu

FAN
ON   AUTO

OFF   HEAT
COOL   EmH

VIVE

INTUITIVE FUNCTIONALITY

Vive™ products respond to every phase of life with corresponding comfort and style. Our cutting edge temperature management is easy to program and user-friendly, and it communicates with almost any HVAC system. Advanced technology and the large, blue LED display offer timeless appeal with contemporary flair. Experience the exclusive controls that bring maximum performance, efficiency and comfort into the home or commercial setting.

VIVE
COMFORT ™

	700 SERIES							
	TP-N-701	**TP-P-705**	**TP-N-721**	**TP-P-725**	**TP-N-751**	**TP-S-755**	**TP-S-755H**	**TP-S-755R**
PROGRAMMING OPTIONS **5/1/1** M–F, SAT & SUN **NP** Non-Programmable	NP	5/1/1	NP	5/1/1	NP	5/1/1 NP	5/1/1 NP	5/1/1 NP
HEAT STAGES	1	1	2	2	3*	3*	3*	3*
COOL STAGES	1	1	1	1	2	2	2	2
GAS, ELECTRIC OR OIL	•	•			•	•	•	•
HEAT PUMP	•	•	•	•	•	•	•	•
AUXILIARY HEAT			•	•	•	•	•	•
EMERGENCY HEAT			•	•	•	•	•	•
CONVENTIONAL HEAT/COOL	•	•			•	•	•	•
MILLIVOLT	•	•			•	•	•	•
BATTERY POWERED	•	•	•	•	•	•	•	•
24V POWER (HARDWARE)	•	•	•	•	•	•	•	•
DUAL FUEL COMPATIBLE			S**	S**	S**	S**	S**	H**
DISPLAY SIZE (SQUARE INCHES)	4"	4"	4"	4"	6"	6"	6"	6"
FILTER CHANGE REMINDER		•	•	•	•	•	•	•
ROOM TEMPERATURE CALIBRATION	•	•	•	•	•	•	•	•
MINIMUM COMPRESSOR RUN TIME		•	•	•	•	•	•	•
COMPRESSOR SHORT CYCLE DELAY	•	•	•	•	•	•	•	•
ADJUSTABLE HEATING TEMPERATURE SWING	•	•	•	•	•	•	•	•
ADJUSTABLE COOLING TEMPERATURE SWING	•	•	•	•	•	•	•	•
PROGRAMMABLE FAN						•	•	•
ADJUSTABLE SETPOINT LIMITS						•	•	•
AVERAGING AND REMOTE SENSOR CAPABLE								•
HUMIDITY CONTROL							•	
5-YEAR WARRANTY	•	•	•	•	•	•	•	•
TERMINALS	Rh W Rc G C B Y O	Rh W Rc G C B Y O	R E C G Y B W2 O	R E C G Y B W2 O	Rh W/E Rc W2 C G Y B Y2 O	Rh W/E Rc W2 C G Y B Y2 O	Rh W2 Rc G C B Y O Y2 H W/E D	Rh W2 Rc G C B Y O Y2 S1 W/E S2
ACCESSORIES	**TP-119** Universal Wall Plate (5 pack), **TP-ROS-250S** Tethered Outdoor Temp Sensor & **TP-RIS-251S** Tethered Indoor Temp Sensor							

*3 heat stages for heat pump or 2 heat stages for conventional.
**H—Dual fuel hardware balance point. Requires Outdoor Temperature Sensor accessory TP-ROS-250S. S—Dual fuel software setting.

- 5-year warranty coverage
- Universal system compatibility
- Easy-to-read backlit LED display
- Universal base plate with color-coded terminals

ENHANCE CUSTOMER RELATIONSHIPS

All Vive™ controls have a removable badge that can be easily replaced with one featuring customized business information. Large inventory purchases are NOT required to take advantage of our private label program. It's easy and free regardless of how many units are purchased!

VIVE ™