

WIFI THERMOSTAT MADE EASY & AFFORDABLE





Millions of TP-N-701 thermostats are in homes across the nation. Not because of all of the bells and whistles it offers, but because it is Simple. Simple to install. Simple to operate. Simple to sell. The exact same logic was applied while designing the TP-S-701i. Installation is a breeze. Programming is optional. WIFI is optional. Comfort guaranteed.



Easy Setup

If you know how to install any Vive thermostat than you know how to install a connected model. The quickstart guide will walk the homeowner through the WIFI linking procedure.



Universal Subbase

Fast, easy upgrade from existing Vive thermostats. No additional wiring necessary as long as C is connected.



Private Label

Contractor contact info displayed in mobile app and on magnetic badge of thermostat to generate return business.



WIFI Optional

All thermostats are fully functional without internet access. Unknown network password? New construction? No problem. Vive will help the homeowner get it connected when they get home.



Smart Grid Capable

Works with many utility incentive programs. Learn more from your professional installer or Vive representative.



Active Alerts

Receive alerts from anywhere. High and low temp. limits, connection status, and more.



1-800-776-1635 | VIVECOMFORT.COM



WIFI Thermostat Application Guide																			
VIVE Model #	NP Non-progammable	100	Ges of Hear	Pestor Cool	Comos Nuith Comos Nuith Comos	Die Oniole Wind	446 520 00 550 000	Filte. Change and the state	Room To Remin	Vation Derature	Alune ature C	Ken Disch	Dod Lockout	vooint Linii	mon Juns	Mchange Creekennane	· ,	ð Terminals	
TP-S-701i	<mark>NP</mark> **	1	1		•	4			•	•	•			•		•		Rh, Rc, C, Y, W, G, B, (C
Gas or Oil Heat							Yes	5	24 Volt Heat Only Systems							Yes			
Electric Furnace							Yes	Yes 24 Volt Heat & Cool Systems							Yes				
Heat Pump (no Aux. or Emergency Heat)							Yes	5	Cool Only Systems							Yes			
Heat Pump (with Aux.)							Nc)	Light Commercial Features								No		
Multi-stage Systems							Nc)	Millivolt									No	

Programming ** = Programming only available from the web app

Specifications

The display range of temperature The control range of temperature	
Load rating	
Display accuracy	1 amp per terminal, 1.5 amp maximum all terminals combined 1°F
Swing (cycle rate of differential)	
	Cooling is adjustable from 0.2°F to 2.0°F
Power Source	
Operating humidity	
Dimensions of Thermostat	
WIFI Module	Supporting 802.11 B/G/N Standards
Frequency	
	Image: Contract of the second seco

Smart Grid Capable

Utility companies offer rebates, rate reductions and other incentives to homeowners who opt into demand response programs. These programs allow the utility companies to scale back energy usage during peak time periods. To learn more contact your professional technician or local Vive sales representative.

Save from Anywhere

Control and monitor the system's performance from anywhere. Homeowners can choose to receive tips on ways to maximize energy efficiency throughout the year.

The Active Alerts send notifications to your smart device if the system is not working correctly.



TP-S-701i WIFI THERMOSTAT



v. 1510

1-800-776-1635 | VIVECOMFORT.COM