

# WARD GASKET

## Neoprene Tape Gasket

GSK NT

### About Ward Neoprene Gasket

Ward Neoprene Gasket is a closed cell industrial foam comprised of neoprene, PVC and nitrile. It is manufactured in continuous rolls resulting in greater yield of parts and lower costs. And it has good chemical resistance and is flame rated.

### Specifications

**ASTM D 1056-68:** SCE 41

**ASTM D 1056-85, 91, 98:** 2C1

**UL 94 HF-1:** LISTED,  $\geq$  .058"

**UL 94 VO:** LISTED,  $\geq$  .456"

**UL 94 HBF:** PASS

**FMV55-302:** PASS

### Physical Properties

**Color:** Black

**Dimensions (T x W x L):** .25in x .75in x 15ft (.6cm x 1.9cm x 4.6m)

**Compression Deflection @ 25% (ASTM D 1056):** 2.0 to 5.0 psi (14 to 34 kPa)

**Density (ASTM D 3575):** 3.5 to 5.0 lbs/ft<sup>3</sup> (.056 to .080 g/cm<sup>3</sup>)

**Compression Set (ASTM D 1056):** 40%

**Water Absorption - Maximum Weight Change (ASTM D 1056):** 10%

**Temperature Range:** -40° to 200°F (-40° to 93.3°C)

**Tensile Strength (ASTM D 412):** 50 psi (345 kPa)

**Elongation Minimum (ASTM D 412):** 100%

**Heat Aging - Change in Compression Deflection (ASTM D 1056):** +/- 30%

The information contained herein we believe is correct to the best of our knowledge and tests. This information is furnished as a guide for selecting materials. Ward Industries disclaims liability for results or use of this information. It is the customer's responsibility to obtain and test samples when determining suitability of material for a particular application.

JOB NAME: _____	SUBMITTED BY: _____
LOCATION: _____	
ARCHITECT: _____	
ENGINEER: _____	
CONTRACTOR: _____	

**WARD™**  
**INDUSTRIES**

5030 Corporate Exchange Blvd SE • Grand Rapids MI 49512  
T (800) 624-8642 • F (800) 972-1421 • [www.wardind.com](http://www.wardind.com)